

PRODUCT DESCRIPTION

Lignum Fusion Twelve V Premium

Laminated Wooden Flooring

| PROPERTY | INFORMATION |
|------------------------------|---|
| Dimension | 1215 x 196 x 12 mm |
| Packing | Pack quantity = 1.85 m ² 12 boards per pack Pack weight 15 kg |
| Production | Direct pressure, melamine impregnated Decorative paper onto high density fibreboard core. |
| Laying | DocLoc glueless locking system Must be laid as a floating floor (see instructions) |
| Classification (BS EN 13329) | 23: Heavy domestic use |

Greige Oak 12V


PRODUCT SPECIFICATION HDF CORE

| FACTOR | STANDARD | COMMENTS |
|------------------|----------|----------------------|
| 24 hour swelling | EN 622-5 | < 17% |
| Bending strength | EN 622-5 | 23 N/mm ² |
| Moisture content | EN 622-1 | 4 - 11 % |
| Formaldehyde | EN 622-1 | ≤ 8 (Class E1) |
| Internal bond | EN 622-5 | 1 N/mm ² |

PRODUCT SPECIFICATION LAMINATED FLOORBOARDS

| | | |
|-------------------|-------------|------------------------------|
| Abrasion | EN 13329 | AC4 |
| Impact resistance | EN 13329 | ≥ IC 1 |
| Stain resistance | EN 438.2.15 | Group 1&2: 5 Group 3: 4 |
| Edge swelling | EN 13329 | ≤ 18 % |

Wood Innovations 52 Newry Road, Warrenpoint, County Down, N. Ireland. BT34 3LD

Tel: 028 4177 3366

Email: sales@woodinnovations.co.uk www.woodinnovations.com