



Declaration of Performance
for product Plywood 18mm
DoP-XH-CE-18

1	Identification code :	Brown/Black Film Faced plywood,eucalyptus-poplar core, A/A grade 2500X1250X18MM Phenolic glue E1	
2	Batch-/Serial number		
3	Intendent use:	Internal use as structural components in Humid conditions	
4	Harmonized technical specification	EN 13986:2004+A1:2015	
5	Manufacturer:	Xuzhou Xinheng Wood Co.,Ltd/Guanhu Town,Pizhou City,Jiangsu,China	
6	System of Assessment and verification of constancy of performance (AVCP)	2+	
7	Notified body:	EPH	
	CE Certificate N	0766-CPR-580	
	UKCA Certificate N	0836-CPR-22/F6028	
8	Declared performance		
Essential characteristics		Performance	Harmonized technical specification
Bending strength parallel (N/mm ²)		50	ITT According to EN 310
perpendiculare (N/mm ²)		45	
Bending stiffness(Modulus Elasticity) parallel (N/mm ²)		5550	
perpendiculare (N/mm ²)		4680	
Classification according to EN636		F20/15 E40/25	EN636
Bonding quality		Class 3	ITT(EN314-1/2)
Durability (moisture resistance) (N/mm ²)		1.22	EN314-1/2 Section 6.6.5
Moisture Content (Up to 14) (%)		14	EN 322
Density		580	EN 323
Realease of Formaldehyde		E1	EN 13986 Annex B,Note 2
Reaction to fire		Declared:D-s2,d0	
<p>The performance of the product(products)is in conformity with the declared performance This declaration of performance is issued the sole responsibility of the manufacturer,identified above. Signed for and behalf of the manufactured by:igned for and behalf of the manufactured by: MA CONG Control Manager (name and function) Town Jan. 20th,2023 (place and date of issue)</p> <div style="display: flex; justify-content: space-between; align-items: center;"> <div style="text-align: center;">  </div> <div style="text-align: center;">  </div> <div style="text-align: right;"> <p>GuanHu</p> </div> </div>			