SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2015/830

PUR CLEANER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PUR CLEANERRegistration number REACH: Not applicable (mixture)Product type REACH: Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Detergent according to Regulation (EC) No 648/2004

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

TEC7* Industrielaan 5B B-2250 Olen S +32 14 85 97 37 H +32 14 85 97 38 info@tec7.be *TEC7 is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V. Industrielaan 5B B-2250 Olen ☎ +32 14 85 97 37 ➡ +32 14 85 97 38 info@tec7.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) : +32 14 58 45 45 (BIG)


SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.

2.2. Label elements





P251 P405

Store locked up.

P410 + P412 P501

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F. Dispose of contents/container in accordance with local/regional/national/international regulation.

Supplemental information FUH066

Repeated exposure may cause skin dryness or cracking.

Do not pierce or burn, even aft er use.

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
acetone 01-2119471330-49	67-64-1 200-662-2	C>25 %	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Constituent
isobutane 01-2119485395-27	75-28-5 200-857-2	C>1 %	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
propane 01-2119486944-21	74-98-6 200-827-9	C>1 %	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
(1,3-butadiene, conc<0.1%)					

(1) For H-statements in full: see heading 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Wash immediately with lots of water. Soap may be used. Do not apply (chemical) neutralizing agents without medical advice. Take victim to a doctor if irritation persists.

After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Do not apply (chemical) neutralizing agents without medical advice. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Do not induce vomiting. Do not apply (chemical) neutralizing agents without medical advice. Consult a doctor/medical service if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms After inhalation:

EXPOSURE TO HIGH CONCENTRATIONS: Feeling of weakness. Central nervous system depression. Dizziness. Narcosis. Excited/restless. Drunkenness. Disturbed motor response. Headache. Respiratory difficulties. Disturbances of consciousness.

After skin contact:

ON CONTINUOUS EXPOSURE/CONTACT: Dry skin. Cracking of the skin.

After eye contact:

Irritation of the eye tissue. After ingestion:

No effects known

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

Reason for revision: 3; 5; 15

Publication date: 2016-12-14 Date of revision: 2019-02-18

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher.

5.1.2 Unsuitable extinguishing media:

Small fire: Quick-acting CO2 extinguisher, Water (water can be used to control jet flame), Foam. Major fire: Water (water can be used to control jet flame), Foam.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistant risk of physical explosion.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective goggles. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosion proof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel See heading 8.2

6.1.2

Protective equipment for emergency responders

Gloves. Protective goggles. Protective clothing.

See heading 8.2

6.2. Environmental precautions

Dam up the liquid spill. Use appropriate containment to avoid environmental contamination.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into a non combustible material e.g.: sand/earth. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Fireproof storeroom. Keep out of direct sunlight. Meet the legal requirements. Max. storage time: 1 year(s)

7.2.2 Keep away from:

Heat sources, ignition sources, oxidizing agents, (strong) acids, (strong) bases.

7.2.3 Suitable packaging material:

Aerosol

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

Reason for revision: 3; 5; 15

Publication date: 2016-12-14 Date of revision: 2019-02-18

Revision number: 0001

ID CIEANED

Belgium Acétone Time-weighted average exposure limit 8 h Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1- C3) Time-weighted average exposure limit 8 h Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1- C3) Time-weighted average exposure limit 8 h Acetone Time-weighted average exposure limit 8 h The Netherlands Short time value Aceton Time-weighted average exposure limit 8 h (Public occupational exposure Time weighted average exposure limit 8 h (Public occupational exposure 501 pp Binit value) Time-weighted average exposure limit 8 h (Public occupational exposure 501 pp Binit value Short time value (Public occupational exposure limit value) 1002 pp Short time value (Public occupational exposure limit value) 1002 pp 500 pp France Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante) 500 pp Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire sourage exposure limit 8 h (VRC: Valeur ré	Acetone		Time-weighted average e	exposure limit 8 h (Indic	ative occupational	500 ppm
Belgium Time-weighted average expoure limit 8 h \$00 pp Acétone Time-weighted average expoure limit 8 h \$200 pp Hydrocarbures aliphatiques sous forme gazeuse: (Alcase CL- Time-weighted average exposure limit 8 h \$200 pp Short time value \$200 pp \$200 pp \$200 pp Short time value \$200 pp \$200 pp \$200 pp Short time value \$200 pp \$200 pp \$200 pp Short time value \$200 pp \$200 pp \$200 pp Short time value \$200 pp \$200 pp \$200 pp Short time value \$200 pp \$200 pp \$200 pp France Time-weighted average exposure limit 8 h (VaCL valuer reglementaire \$200 pp France Time-weighted average exposure limit 8 h (VACL valuer reglementaire \$200 pp Short time value (Public occupational exposure limit 8 h) (VACL valuer reglementaire \$200 pp Short time value (Public occupational exposure limit 8 h) (VACL valuer reglementaire \$200 pp Short time value (Public occupational exposure limit 8 h) (VACL valuer reglementaire \$200 pp Short time value (Public occupational exposure limit 8 h) (VACL valuer reglementaire \$200 pp Short time value (Publ			Time-weighted average e	exposure limit 8 h (Indic	ative occupational	1210 mg/r
Acetoone Imme-weighted average exposure limit 8 h 900 pp Productabues aliphatiques sous forme guzeuse: (Alcanes CL- Imme-weighted average exposure limit 8 h 920 pp Short time value 930 pp Short time value 930 pp The Netherlands Imme-weighted average exposure limit 8 h 930 pp Aceton Imme-weighted average exposure limit 8 h 930 pp Short time value 930 pp 930 pp Short time value 930 pp 930 pp The Netherlands Imme-weighted average exposure limit 8 h 930 pp Acetoon Imme-weighted average exposure limit 8 h 930 pp Imme value [Public occupational exposure 501 pp Short time value Public occupational exposure 500 pp France Imme value [Public occupational exposure 500 pp Contarganatei Short time value (Public occupational exposure 1000 pp Short time value (Public occupational exposure 1000 pp 1000 pp Short time value (Public occupational exposure 1000 pp 1000 pp Short time value (Public occupational exposure 1000 pp 1000 pp Short time value (Public occupational exposure 1000 pp 1000 pp Short time value (Public occupational exposure 1000 pp Acetoone </td <td></td> <td></td> <td>exposure limit value)</td> <td></td> <td></td> <td></td>			exposure limit value)			
Time-weighted average exposure limit & h 1220 m Productabues aliphatiques sous forme gazeuse: (Alcanes Ci. Time veighted average exposure limit & h 200 p C(1) Short time value 860 pp C(2) Short time value 800 pp Short time value 800 pp Aceton Time weighted average exposure limit & h 1000 pp The Netherlands Time weighted average exposure limit & h 201 pp Aceton Time weighted average exposure limit & h 202 pp Short time value 300 pp 300 pp Short time value 300 pp 300 pp Short time value 300 pp 300 pp Short time value (Public occupational exposure limit value) 3002 pp Short time value (Public occupational exposure limit value) 3000 pp Short time value (Public occupational exposure limit value) 3000 pp Short time value (Public occupational exposure limit value) 3000 pp Short time value (Public occupational exposure limit value) 3000 pp Short time value (Public occupational exposure limit value) 3000 pp Short time value (Public occupational exposure limit value) 3000 pp Short time value (•		Time weighted average of	vnosuro limit 9 h		500 ppm
Short time value 2020 program hydrocarbures alighatiques sous forme gazeuse: (Alcanes CL- G) Time-weighted average exposure limit 8 h 2020 program C3) Short time value 980 ppo Short time value 980 ppo The Netherlands Time-weighted average exposure limit 8 h (Public accupational exposure limit value) 301 ppi The Netherlands Time-weighted average exposure limit 8 h (Public accupational exposure limit value) 302 ppi France Time-weighted average exposure limit 8 h (Public accupational exposure limit value) 302 ppi France Time-weighted average exposure limit 8 h (Public accupational exposure limit value) 302 ppi Short time value (Public accupational exposure limit 8 h (PASC: Valeur réglementaire contraignante) 3000 pp Short time value (PAC: Valeur réglementaire contraignante) 3000 pp Short time value (PAC: Valeur réglementaire contraignante) 3000 pp Short time value (PAC: Valeur réglementaire contraignante) 3000 pp Short time value (PAC: Valeur réglementaire contraignante) 3000 pp Short time value (PAC: Valeur réglementaire contraignante) 3000 pp Short time value (PAC: Valeur réglementaire contraignante) 3000 pp S	Acetone					
Improve the sale photogenes of the solution of the solu						.
nydroczabures aliphutiques sous forme gzzeuse: (Alcanes CL G3) Time-weighted average exposure limit 8 h Time-weighted average exposure limit 8 h Time-weighted average exposure limit 8 h Time-weighted average exposure limit 8 h Time weighted average exposure limit 8 h Time						
C3) Short time value 980 pp Short time value 2370 m Aceton Time-weighted average exposure limit 8 h (Public occupational exposure limit value) 1202 m Time weighted average exposure limit 8 h (Public occupational exposure limit value) 1202 m Short time value (Public occupational exposure limit value) 1202 m France Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante) 1200 m Rectone Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante) 1200 m Short time value (Public devergate exposure limit 8 h (VRC: Valeur réglementaire contraignante) 1200 m Short time value (VRC: Valeur réglementaire contraignante) 1200 m Short time value (VRC: Valeur réglementaire contraignante) 1200 m Short time value (VRC: Valeur réglementaire contraignante) 1200 m Short time value (VRC: Valeur réglementaire contraignante) 1200 m Short time value (VRC: Valeur réglementaire contraignante) 1200 m roman Time-weighted average exposure limit 8 h (TR65 800) 1200 m roppan Time-weighted average exposure limit 8 h (TR65 800) 1300 m VK Time-weighted average exposure limit 8 h (Workplace exposure limit 8 h (Workplace exposure limit 8 h (Wor		famma (Alaama C1	-	un e e un e lineite O h		-
Aceton 2370 m Aceton Imme-weighted average exposure limit 8 h (Public occupational exposure 1210 m limit value) 1200 m limit value) Short time value (Public occupational exposure 1210 m limit value) 1200 m limit value) 1200 m limit value) Aceton Imme-weighted average exposure limit 8 h (Public occupational exposure 120 m limit value) 1200 m limit value) Aceton Imme-weighted average exposure limit 8 h (VRC: valeur réglementaire contraignante) 1200 m limit value) Aceton Imme-weighted average exposure limit 8 h (VRC: valeur réglementaire contraignante) 1200 m limit 8 h (VRC: valeur réglementaire contraignante) 1200 m limit 8 h (VRC: valeur réglementaire contraignante) 1200 m limit 8 h (VRC: valeur réglementaire contraignante) 1200 m limit 8 h (VRC: valeur réglem		forme gazeuse: (Alcanes C1-		exposure limit 8 h		
The Netherlands Time-weighted average exposure limit 8 h (Public occupational exposure [212 m limit value) 501 pp Aceton Time-weighted average exposure limit 8 h (Public occupational exposure [212 m limit value) 1002 pp France Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire [900 pp 500 pp France Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire [900 pp 500 pp Acetone Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire [900 pp 500 pp Germany Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante) 2420 m Short time value (VRC: Valeur réglementaire contraignante) 2420 m 1000 pp Short time value (VRC: Valeur réglementaire contraignante) 2420 m 1000 pp Short time value (VRC: Valeur réglementaire contraignante) 2420 m 1000 pp Short time-weighted average exposure limit 8 h (TRGS 500) 1000 pp 1000 pp Time-weighted average exposure limit 8 h (TRGS 500) 1200 m 1000 pp Time-weighted average exposure limit 8 h (TRGS 500) 1200 m 1000 pp Time-weighted average exposure limit 8 h (TRGS 500) 1200 m 1000 pp Opan Time-			Short time value			980 ppm
Aceton Imme-weighted average exposure limit & h (Public occupational exposure limit value) 501 pp Imme value(Public occupational exposure limit value) 1210 m Imme value France Imme value (Public occupational exposure limit value) 1202 pp Short time value (Public occupational exposure limit value) 1210 m Acétone Time-weighted average exposure limit & h (VRC: Valeur réglementaire contraignante) 1200 pp Short time value (Public occupational exposure limit value) 1202 pp 2420 m Acétone Time-weighted average exposure limit & h (VRC: Valeur réglementaire contraignante) 1200 pp Short time value (VRC: Valeur réglementaire contraignante) 1200 pp 2420 m Germany Imme-weighted average exposure limit & h (TRCS 500) 1000 pp Short time value (VRC: Valeur réglementaire contraignante) 1200 pp 2400 m Aceton Time-weighted average exposure limit & h (TRCS 500) 1000 pp 1000 pp France Time-weighted average exposure limit & h (TRCS 500) 1000 pp 1000 pp VK M 1000 pp 1000 pp 1000 pp 1000 pp 1000 pp 1000 pp 1000 pp 1000 pp VK M 1000 pp 1000 pp			Short time value			2370 mg/r
Imit: value) Imit: value) Imit: value) Time:-weighted average exposure limit & h (Public occupational exposure 1002 p) Short time value (Public occupational exposure limit value) 1202 m) France Imit: value (Public occupational exposure limit value) 2420 m) Acétone Imit: value (Public occupational exposure limit value) 2420 m) Germany Imit: value (Public occupational exposure limit & h (VRC: Valeur réglementaire contraignante) 1000 p) Short time value (VRC: Valeur réglementaire contraignante) 1000 p) 500 p) Germany Imit: value (VRC: Valeur réglementaire contraignante) 1000 p) Aceton Time-weighted average exposure limit & h (TRGS 900) 1000 p) toobutan Time-weighted average exposure limit & h (TRGS 900) 1000 p) rime:-weighted average exposure limit & h (TRGS 900) 1000 p) 1000 p) fume:-weighted average exposure limit & h (TRGS 900) 1000 p) 1000 p) fume:-weighted average exposure limit & h (TRGS 900) 1000 p) 1000 p) fume:-weighted average exposure limit & h (TRGS 900) 1000 p) 1000 p) fume:-weighted average exposure limit & h (TRGS 900) 1000 p) 1000 p)	The Netherlands					
Time-weighted average exposure limit 8 h (Public occupational exposure 22.0 m Short time value (Public occupational exposure limit value) 1002 p Short time value (Public occupational exposure limit value) 242.0 m France Imme-weighted average exposure limit 8 h (VRC: Valeur reglementaire contraignante) 1002 pp Acétone Imme-weighted average exposure limit 8 h (VRC: Valeur reglementaire contraignante) 1000 pp Short time value (VRC: Valeur réglementaire contraignante) 1000 pp 242.0 m Short time value (VRC: Valeur réglementaire contraignante) 1000 pp 242.0 m Short time value (VRC: Valeur réglementaire contraignante) 1000 pp 242.0 m Short time value (VRC: Valeur réglementaire contraignante) 1000 pp 1000 pp Isobutan Time-weighted average exposure limit 8 h (TRGS 500) 1000 pp Propan Time-weighted average exposure limit 8 h (TRGS 500) 1000 pp VL Mcetone Time-weighted average exposure limit 8 h (TRGS 500) 1000 pp VL Mcetone Time-weighted average exposure limit 8 h (TRGS 500) 1000 pp VL Mcetone Time-weighted average exposure limit 8 h (TRGS 500) 1000 pp <	Aceton		0 0	exposure limit 8 h (Publi	c occupational exposure	e 501 ppm
Short time value (Public accupational exposure limit value) 1002 pg Short time value (Public accupational exposure limit value) 2420 m Acétone Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante) 500 pp Short time value (VRC: Valeur réglementaire contraignante) 1000 pg Short time value (VRC: Valeur réglementaire contraignante) 1000 pg Short time value (VRC: Valeur réglementaire contraignante) 1000 pg Short time value (VRC: Valeur réglementaire contraignante) 1000 pg Short time value (VRC: Valeur réglementaire contraignante) 1000 pg Short time value (VRC: Valeur réglementaire contraignante) 1000 pg Short time value (VRC: Valeur réglementaire contraignante) 1000 pg Short time value (VRC: Valeur réglementaire contraignante) 1000 pg Short time value (VRC: Valeur réglementaire contraignante) 1000 pg Short time value (VRC: Valeur réglementaire contraignante) 1000 pg Short time value (VRC: Valeur réglementaire contraignante) 1000 pg Short time-weighted average exposure limit 8 h (TRGS 900) 1000 pg VK Imme-weighted average exposure limit 8 h (Workplace exposure limit 12 h (Tid40/2005)) 1500 pg Short ti				exposure limit 8 h (Publi	c occupational exposure	e 1210 mg/r
Short time value (Public occupational exposure limit value) 2420 m France Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante) 1210 m Acétone Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante) 1200 m Short time value (VRC: Valeur réglementaire contraignante) 2420 m Germany Short time value (VRC: Valeur réglementaire contraignante) 2420 m Keeton Time-weighted average exposure limit 8 h (TRGS 900) 1000 p Isobutan Time-weighted average exposure limit 8 h (TRGS 900) 1000 p Propan Time-weighted average exposure limit 8 h (TRGS 900) 1000 p Propan Time-weighted average exposure limit 8 h (TRGS 900) 1000 p VK Time-weighted average exposure limit 8 h (TRGS 900) 1000 p Acetone Time-weighted average exposure limit 8 h (TRGS 900) 1000 p VK Time-weighted average exposure limit 8 h (TRGS 900) 1000 p VK Time-weighted average exposure limit 8 h (TRGS 900) 1000 p VK Time-weighted average exposure limit 8 h (TRGS 900) 1000 p VK Time-weighted average exposure limit 8 h (TRGS 900) 1000 p VK Time-weighted average exposure limit 8 h (TV - Adopted Value) 1000 p VK Time-weighted average exposure limit 8 h (TV - Adopted Val						1
Acêtone Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante) 500 pp Acêtone Contraignante) Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante) 1000 pp Short time value (VRC: Valeur réglementaire contraignante) 1000 pp 500 pp Germany Short time value (VRC: Valeur réglementaire contraignante) 2420 m Aceton Time-weighted average exposure limit 8 h (TRGS 900) 500 pp Sobutan Time-weighted average exposure limit 8 h (TRGS 900) 1000 pp Sobutan Time-weighted average exposure limit 8 h (TRGS 900) 1000 pp Propan Time-weighted average exposure limit 8 h (TRGS 900) 1000 pp VK Time-weighted average exposure limit 8 h (TRGS 900) 1000 pp VK Time-weighted average exposure limit 8 h (TRGS 900) 1800 m VK Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) 1500 pp VK Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) 1500 pp VIA (TV-ACGH) Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) 1500 pp VIA (TV-ACGH) Time-weighted average exposure limit 8 h (TIV - Adopted Value) 250 pp			· · · · · · · · · · · · · · · · · · ·			1002 ppm
Acétone Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante) 500 ppi init 8 h (VRC: Valeur réglementaire contraignante) 1210 m Germany Short time value (VRC: Valeur réglementaire contraignante) 2420 m Germany Time-weighted average exposure limit 8 h (TRGS 900) 500 ppi sobutan Time-weighted average exposure limit 8 h (TRGS 900) 1200 m Isobutan Time-weighted average exposure limit 8 h (TRGS 900) 1200 m Propan Time-weighted average exposure limit 8 h (TRGS 900) 1200 m VK Time-weighted average exposure limit 8 h (TRGS 900) 1800 m VK Time-weighted average exposure limit 8 h (TRGS 900) 1800 m VK Time-weighted average exposure limit 8 h (Workplace exposure limit 1210 m 500 ppi (EH40/2005)) 1500 ppi (EH40/2005)) Short time value (Workplace exposure limit 8 h (Workplace exposure limit 1210 m 1210 m 1210 m Germany Time-weighted average exposure limit 8 h (Workplace exposure limit 1210 m 1500 ppi (EH40/2005)) 1500 ppi (Short time value (Workplace exposure limit 8 h (Workplace exposure limit 1210 m 1210 m Jacetone Time-weighted average exposure limit 8 h (TRGS 900 ppi (Short time value (Workplace exposure limit 8 h (TRGS 900 ppi (Short time value (Workplace exposure limit (EH40/2005)) 1500 ppi (Shor			Short time value (Public o	occupational exposure I	imit value)	2420 mg/r
Acétone Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante) 500 ppi init 8 h (VRC: Valeur réglementaire contraignante) 1210 m Germany Short time value (VRC: Valeur réglementaire contraignante) 2420 m Germany Time-weighted average exposure limit 8 h (TRGS 900) 500 ppi sobutan Time-weighted average exposure limit 8 h (TRGS 900) 1200 m Isobutan Time-weighted average exposure limit 8 h (TRGS 900) 1200 m Propan Time-weighted average exposure limit 8 h (TRGS 900) 1200 m VK Time-weighted average exposure limit 8 h (TRGS 900) 1800 m VK Time-weighted average exposure limit 8 h (TRGS 900) 1800 m VK Time-weighted average exposure limit 8 h (Workplace exposure limit 1210 m 500 ppi (EH40/2005)) 1500 ppi (EH40/2005)) Short time value (Workplace exposure limit 8 h (Workplace exposure limit 1210 m 1210 m 1210 m Germany Time-weighted average exposure limit 8 h (Workplace exposure limit 1210 m 1500 ppi (EH40/2005)) 1500 ppi (Short time value (Workplace exposure limit 8 h (Workplace exposure limit 1210 m 1210 m Jacetone Time-weighted average exposure limit 8 h (TRGS 900 ppi (Short time value (Workplace exposure limit 8 h (TRGS 900 ppi (Short time value (Workplace exposure limit (EH40/2005)) 1500 ppi (Shor	France					
Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante) 1200 m Germany Time-weighted average exposure limit 8 h (TRGS 900) 2200 m Aceton Time-weighted average exposure limit 8 h (TRGS 900) 1200 m Time-weighted average exposure limit 8 h (TRGS 900) 1200 m Propan Time-weighted average exposure limit 8 h (TRGS 900) 1200 m Propan Time-weighted average exposure limit 8 h (TRGS 900) 1200 m VL Time-weighted average exposure limit 8 h (TRGS 900) 1200 m VE Time-weighted average exposure limit 8 h (TRGS 900) 1200 m VL Time-weighted average exposure limit 8 h (TRGS 900) 1200 m VL Time-weighted average exposure limit 8 h (TRGS 900) 1200 m VL Time-weighted average exposure limit 8 h (TRGS 900) 1200 m VL Time-weighted average exposure limit 8 h (TRGS 900) 1200 m VL Short time value (Workplace exposure limit 8 h (TRGS 900) 1200 m VL Short time value (Workplace exposure limit 8 h (Vorkplace exposure limit 121 m 500 pp Short time value (Workplace exposure limit 8 h (Vorkplace exposure limit 122 m 500 pp Short time value (Workplace exposure limit 8 h (TRGS 900) 3620 m Justane, all isomers Short time value (TLV - Adopted Value) 250 pp Bu				exposure limit 8 h (VRC:	Valeur réglementaire	500 ppm
contraignance) Image: Contraignance) <td></td> <td></td> <td></td> <td>exposure limit 8 h (VRC:</td> <td>Valeur réglementaire</td> <td>1210 mg/r</td>				exposure limit 8 h (VRC:	Valeur réglementaire	1210 mg/r
Short time value (VRC: Valeur réglementaire contraignante) 2420 m Germany Time-weighted average exposure limit 8 h (TRGS 900) 500 pp) Isobutan Time-weighted average exposure limit 8 h (TRGS 900) 1000 pp Isobutan Time-weighted average exposure limit 8 h (TRGS 900) 1000 pp Propan Time-weighted average exposure limit 8 h (TRGS 900) 1000 pp Rectore Time-weighted average exposure limit 8 h (TRGS 900) 1000 pp UK Time-weighted average exposure limit 8 h (TRGS 900) 1000 pp Acetone Time-weighted average exposure limit 8 h (Workplace exposure limit 1 (EH40/2005)) 1500 pp Time-weighted average exposure limit 8 h (Workplace exposure limit 1 (EH40/2005)) 1500 pp 1210 m Acetone Time-weighted average exposure limit 8 h (Workplace exposure limit 1 (EH40/2005)) 1500 pp Short time value (Workplace exposure limit 1 (EH40/2005)) 1500 pp 1500 pp Butane, all isomers Short time value (Workplace exposure limit 8 h (TLV - Adopted Value) 250 pp Butane, all isomers Short time value (TLV - Adopted Value) 1000 pp Di Attonab biobizical limit values Short time value (TLV - Adopted Value) 1000 pp Di Attonab biobizical limit values Sh			contraignante)	•	•	1000 ppm
Germany Aceton Time-weighted average exposure limit 8 h (TRGS 900) 500 pp Aceton Time-weighted average exposure limit 8 h (TRGS 900) 1200 m Isobutan Time-weighted average exposure limit 8 h (TRGS 900) 1200 m Propan Time-weighted average exposure limit 8 h (TRGS 900) 1000 pp Propan Time-weighted average exposure limit 8 h (TRGS 900) 1000 pp UK Ime-weighted average exposure limit 8 h (TRGS 900) 1000 pp Acetone Time-weighted average exposure limit 8 h (TRGS 900) 1000 pp UK Ime-weighted average exposure limit 8 h (TRGS 900) 1000 pp Acetone Time-weighted average exposure limit 8 h (TRGS 900) 1000 pp Itime value(Volume) S00 pp 1000 pp 11210 m 1210 m (EH40/2005)) Time-weighted average exposure limit 8 h (TRGS 900) 1500 pp Short time value (Workplace exposure limit 8 h (TRGS 900) 1500 pp 1500 pp Jatane, all isomers Short time value (Workplace exposure limit 8 h (TV - Adopted Value) 250 pp B National biological limit values Short time value (TLV - Adopted Value) 1000 pp J National biological limit values Short time value (TLV - Adopted Value)						2420 mg/r
Actoon Time-weighted average exposure limit 8 h (TRGS 900) 500 pp Isobutan Time-weighted average exposure limit 8 h (TRGS 900) 1000 pp Isobutan Time-weighted average exposure limit 8 h (TRGS 900) 1000 pp Propan Time-weighted average exposure limit 8 h (TRGS 900) 1000 pp UK Time-weighted average exposure limit 8 h (TRGS 900) 1800 m UK Ime-weighted average exposure limit 8 h (TRGS 900) 1800 m UK Ime-weighted average exposure limit 8 h (Workplace exposure limit 12 to m 500 pp Acetone Time-weighted average exposure limit 8 h (Workplace exposure limit 12 to m 1210 m (EH40/2005)) Short time value (Workplace exposure limit 8 h (UV + Adopted Value) 1500 pp Short time value (Workplace exposure limit 8 h (UV + Adopted Value) 250 pp 500 pp Butane, all isomers Short time value (TLV - Adopted Value) 250 pp Short time value (TLV - Adopted Value) 1000 pp 1000 pp Datatonal biological limit values Short time value (TLV - Adopted Value) 500 pp Butane, all isomers Short time value (TLV - Adopted Value) 500 pp Datatonal biological limit values Short time value (TLV - Adopted Value) 500 pp <td></td> <td></td> <td>Short time value (vice. ve</td> <td></td> <td>in agnance/</td> <td>2420 1116/1</td>			Short time value (vice. ve		in agnance/	2420 1116/1
Time-weighted average exposure limit 8 h (TRGS 900) 1200 m isobutan Time-weighted average exposure limit 8 h (TRGS 900) 1200 m Propan Time-weighted average exposure limit 8 h (TRGS 900) 1200 m W Time-weighted average exposure limit 8 h (TRGS 900) 1800 m UK Time-weighted average exposure limit 8 h (TRGS 900) 1800 m UK Time-weighted average exposure limit 8 h (TRGS 900) 1800 m Cetone Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) 1500 pi Short time value (Workplace exposure limit 8 h (Workplace exposure limit (EH40/2005)) 1500 pi 1210 m Short time value (Workplace exposure limit (EH40/2005)) 3620 m 3620 m USA (TLV-ACGIH) Time-weighted average exposure limit 8 h (TLV - Adopted Value) 500 pp Butane, all isomers Short time value (TLV - Adopted Value) 500 pp Butane, all isomers Short time value (TLV - Adopted Value) 500 pp D Short time value (TLV - Adopted Value) 1000 p 1000 p D Short time value (TLV - Adopted Value) 500 pp 1000 p Short time value (TLV - Adopted Value) 500 pp 1000 p </td <td>Germany</td> <td></td> <td></td> <td></td> <td></td> <td></td>	Germany					
Imme-weighted average exposure limit 8 h (TRGS 900) 1200 m Isobutan Time-weighted average exposure limit 8 h (TRGS 900) 1000 p Propan Time-weighted average exposure limit 8 h (TRGS 900) 1000 p Imme-weighted average exposure limit 8 h (TRGS 900) 1800 m 1800 m UK Time-weighted average exposure limit 8 h (Workplace exposure limit 8 h (TRGS 900) 1210 m (EH40/2005)) Acetone Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) 1500 p Short time value (Workplace exposure limit 8 h (Workplace exposure limit (EH40/2005)) 1500 p Short time value (Workplace exposure limit (EH40/2005)) 1500 p Short time value (Workplace exposure limit 8 h (TRC 900) 1000 p Use (TLV-ACGIH) Time-weighted average exposure limit 8 h (TRC 900) 1500 p Short time value (TLV - Adopted Value) 500 pp 1000 p Blatane, all isomers Short time value (TLV - Adopted Value) 1000 p Short time value (TLV - Adopted Value) 1000 p 1000 p Dataneal biological limit values Short time value (TLV - Adopted Value) 100 p Short time value (TLV - Adopted Value) Short time value (TLV - Adopted Value)	Aceton		Time-weighted average exposure limit 8 h (TRGS 900)			500 ppm
Propan Time-weighted average exposure limit 8 h (TRGS 900) 2400 m Propan Time-weighted average exposure limit 8 h (TRGS 900) 1000 p ITime-weighted average exposure limit 8 h (TRGS 900) 1800 m UK Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) 500 pp ITime-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) 1210 m (EH40/2005)) 1500 pp Short time value (Workplace exposure limit (EH40/2005)) 1500 pp 3620 m USA (TLV-ACGIH) Acetone Time-weighted average exposure limit 8 h (TV - Adopted Value) 250 pp Acetone Time-weighted average exposure limit 8 h (TV - Adopted Value) 500 pp Butane, all isomers Short time value (TU - Adopted Value) 200 pp Butane, all isomers Short time value (TU - Adopted Value) 1000 pp Short time value (TU - Adopted Value) 1000 pp 1000 pp Aceton (Aceton) Urin: expositionsende, bzw. schichtende 80 mg/l 11/2012 Ständige Senatskom Prüdung gesundheitschälldr Arbeitsstoffe der DFG 25 mg/L 25 mg/L 2.5 ampling methods Product name Test Number Acetone (ketones 1) NIOSH			Time-weighted average exposure limit 8 h (TRGS 900)			
Propan Time-weighted average exposure limit 8 h (TRGS 900) 1000 pp UK Ime-weighted average exposure limit 8 h (TRGS 900) 1800 m UK Ime-weighted average exposure limit 8 h (Workplace exposure limit 1 h (H40/2005)) 500 pp Time-weighted average exposure limit 8 h (Workplace exposure limit 1 h (H40/2005)) Time-weighted average exposure limit 1 h (Workplace exposure limit 1 h (H40/2005)) 1500 pp Short time value (Workplace exposure limit (EH40/2005)) Short time value (Workplace exposure limit 1 h (H40/2005)) 3620 m USA (TLV-ACGIH) Ime-weighted average exposure limit 8 h (TLV - Adopted Value) 250 pp Butane, all isomers Short time value (TLV - Adopted Value) 250 pp Butane, all isomers Short time value (TLV - Adopted Value) 1000 p Butane, all isomers Short time value (TLV - Adopted Value) 1000 p Butane, all isomers Urin: expositionsende, bzw. schichtende 80 mg/l 11/2012 Standige Senatskom Prifung gesundheitsschädlich Arbeitsstoffe der DFG USA (BEI-ACGIH) Imme: end of shift 25 mg/L 255 Acetone (Acetone) Urine: end of shift 259 mg/L 259 Acetone (ketones 1) NIOSH 1300	Isobutan		Time-weighted average exposure limit 8 h (TRGS 900)			
Time-weighted average exposure limit 8 h (TRGS 900) 1800 m UK Ime-weighted average exposure limit 8 h (Workplace exposure limit 1200 m) 500 pp Acetone [EH40/2005)] 1500 pp Time-weighted average exposure limit 8 h (Workplace exposure limit 1210 m 1210 m (EH40/2005)) Short time value (Workplace exposure limit 18 h (Workplace exposure limit 1210 m) 1500 pp USA (TLV-ACGIH) Time-weighted average exposure limit 8 h (TLV - Adopted Value) 250 pp Acetone Time-weighted average exposure limit 8 h (TLV - Adopted Value) 250 pp Butane, all isomers Short time value (TLV - Adopted Value) 500 pp Butane, all isomers Short time value (TLV - Adopted Value) 1000 p J National biological limit values If limit values are applicable and available these will be listed below. Germany Aceton (Aceton) Urin: expositionsende, bzw. schichtende 80 mg/l 11/2012 Ständige Senatskom Prüfung gesundheitsschällich Arbeitsschällich Arbeitsschäll			Time-weighted average exposure limit 8 h (TRGS 900)			
Time-weighted average exposure limit 8 h (TRGS 900) 1800 m UK Ime-weighted average exposure limit 8 h (Workplace exposure limit [EH40/2005)) 500 pp ITime-weighted average exposure limit 8 h (Workplace exposure limit [EH40/2005)) 500 pp ITime-weighted average exposure limit 8 h (Workplace exposure limit [EH40/2005)) 1500 pp Short time value (Workplace exposure limit (EH40/2005)) 1500 pp Short time value (Workplace exposure limit (EH40/2005)) 3620 m USA (TLV-ACGIH) Ime-weighted average exposure limit 8 h (TLV - Adopted Value) 250 pp Butane, all isomers Short time value (TLV - Adopted Value) 500 pp Butane, all isomers Short time value (TLV - Adopted Value) 1000 pp J National biological limit values If limit values are applicable and available these will be listed below. Germany Aceton (Aceton) Urin: expositionsende, bzw. schichtende 80 mg/l 11/2012 Ständige Senatskom Prüfung gesundheitsschädlich Arbeitsschädlich Arbeit	Propan					
Acetone Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) 500 pp/(EH40/2005)) Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) 1210 m (EH40/2005)) Short time value (Workplace exposure limit (EH40/2005)) 1500 pp Short time value (Workplace exposure limit (EH40/2005)) 3620 m Acetone Time-weighted average exposure limit 8 h (TLV - Adopted Value) 250 pp Butane, all isomers Short time value (TLV - Adopted Value) 500 pp Butane, all isomers Short time value (TLV - Adopted Value) 1000 pp D) National biological limit values If limit values are applicable and available these will be listed below. 660 mg/l 11/2012 Ständige Senatskom Germany Aceton (Aceton) Urine: end of shift 25 mg/L 125 mg/L Acetone (Acetone) Urine: end of shift 25 mg/L 25 mg/L Acetone (ketones 1) NIOSH 1300 Acetone (ketones 1) NIOSH 2555 Acetone (volati lorganic gases by Extractive FTIR) NIOSH 2549 Acetone (volati lorganic compounds) NIOSH 2549 Acetone (volati lorganic compounds) NIOSH 8319 3419 Acetone (volati lorganic compounds) NI			Time-weighted average e	exposure limit 8 h (TRGS	5 900)	1800 mg/r
Acetone Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) 500 pp/(EH40/2005)) Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) 1210 m (EH40/2005)) Short time value (Workplace exposure limit (EH40/2005)) 1500 pp Short time value (Workplace exposure limit (EH40/2005)) 3620 m Acetone Time-weighted average exposure limit 8 h (TLV - Adopted Value) 250 pp Butane, all isomers Short time value (TLV - Adopted Value) 500 pp Butane, all isomers Short time value (TLV - Adopted Value) 1000 pp D) National biological limit values If limit values are applicable and available these will be listed below. 660 mg/l 11/2012 Ständige Senatskom Germany Aceton (Aceton) Urine: end of shift 25 mg/L 125 mg/L Acetone (Acetone) Urine: end of shift 25 mg/L 25 mg/L Acetone (ketones 1) NIOSH 1300 Acetone (ketones 1) NIOSH 2555 Acetone (volati lorganic gases by Extractive FTIR) NIOSH 2549 Acetone (volati lorganic compounds) NIOSH 2549 Acetone (volati lorganic compounds) NIOSH 8319 3419 Acetone (volati lorganic compounds) NI	ик					
(EH40/2005)) Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) 1210 m (EH40/2005)) Short time value (Workplace exposure limit (EH40/2005)) 1500 pp Short time value (Workplace exposure limit (EH40/2005)) 3620 m USA (TLV-ACGIH) Time-weighted average exposure limit 8 h (TLV - Adopted Value) 250 pp Butane, all isomers Short time value (TLV - Adopted Value) 500 pp Butane, all isomers Short time value (TLV - Adopted Value) 1000 pp b) National biological limit values If limit values are applicable and available these will be listed below. Germany Aceton (Aceton) Urin: expositionsende, bzw. schichtende 80 mg/l 11/2012 Ständige Senatskom Prüfung gesundheitschädlich Arbeitsstoffe der DFG Usa (BEI-ACGIH) 25 mg/L 25 mg/L Acetone (Acetone) Urine: end of shift 25 mg/L 25 mg/L 25 mg/L 2 Sampling methods Product name Number 3800 Acetone (ketones 1) NIOSH 3800 Acetone (loatin inorganic gases by Extractive FTIR) NIOSH 2549 Acetone (organic compounds) NIOSH 2549 Acetone (volatile Organic compounds) NIOSH 2549 340 319			Time-weighted average of	exposure limit & h (Mor	nlace exposure limit	500 ppm
Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005)) 1210 m Short time value (Workplace exposure limit (EH40/2005)) 1500 pp Short time value (Workplace exposure limit (EH40/2005)) 3620 m USA (TLV-ACGIH) 250 pp Acetone Time-weighted average exposure limit 8 h (TLV - Adopted Value) 250 pp Butane, all isomers Short time value (TLV - Adopted Value) 500 pp Butane, all isomers Short time value (TLV - Adopted Value) 1000 pp b National biological limit values Filmit values are applicable and available these will be listed below. Germany Aceton (Aceton) Urin: expositionsende, bzw. schichtende 80 mg/l 11/2012 Ständige Senatskom Prüfung gesundheitsschädlich Arbeitsstoffe der DFG USA (BEI-ACGIH) 25 mg/L 25 mg/L 25 mg/L Acetone (Acetone) Urine: end of shift 25 mg/L 25 mg/L 2 Sampling methods Number Acetone (ketones 1) NIOSH 1300 Acetone (ketones 1) NIOSH 2800 Acetone (organic and inorganic gases by Extractive FTIR) NIOSH 2540 Acetone (organic and inorganic compounds) NIOSH 2549 Acetone 3400 Acetone </td <td></td> <td></td> <td>• •</td> <td></td> <td>ישופר באטסטוים ווווונ</td> <td>200 hhiii</td>			• •		ישופר באטסטוים ווווונ	200 hhiii
(EH40/2005)) Short time value (Workplace exposure limit (EH40/2005)) 1500 pr Short time value (Workplace exposure limit (EH40/2005)) 3620 m USA (TLV-ACGIH) Acetone Time-weighted average exposure limit 8 h (TLV - Adopted Value) 250 pp Butane, all isomers Short time value (TLV - Adopted Value) 1000 pp b) National biological limit values Ime-weighted average exposure limit 8 h (TLV - Adopted Value) 1000 pp b) National biological limit values Short time value (TLV - Adopted Value) 1000 pp b) National biological limit values Imit values are applicable and available these will be listed below. Germany Aceton (Aceton) Urin: expositionsende, bzw. schichtende 80 mg/l 11/2012 Ständige Senatskom Prüfung gesundheitsschädlict Arbeitsstoffe der DFG USA (BEI-ACGIH) Acetone (Acetone) Urine: end of shift 25 mg/L 25 - 2 Sampling methods - - - - - Product name Test Number - - - - Acetone (ketones 1) NIOSH 2555 - - - - - - - - - - -				exposure limit 8 h (Work	xplace exposure limit	1210 mg/r
Short time value (Workplace exposure limit (EH40/2005)) 1500 pp Short time value (Workplace exposure limit (EH40/2005)) 3620 m USA (TLV-ACGIH) Ime-weighted average exposure limit 8 h (TLV - Adopted Value) 250 pp Butane, all isomers Short time value (TLV - Adopted Value) 500 pp Butane, all isomers Short time value (TLV - Adopted Value) 500 pp b) National biological limit values If limit values are applicable and available these will be listed below. 6ermany Aceton (Aceton) Urin: expositionsende, bzw. schichtende 80 mg/l 11/2012 Ständige Senatskom Prüfung gesundheitsschädlich Arbeitsstoffe der DFG USA (BEI-ACGIH) Acetone (Acetone) Urine: end of shift 25 mg/L 25 mg/L 2 Sampling methods Product name Test Number Acetone (ketones 1) NIOSH 1300 Acetone (ketones 1) NIOSH 2555 Acetone (volatile Organic compounds) NIOSH 2549 Acetone (volatile Organic compounds) NIOSH 2549 3300 Acetone 3419 Acetone (Volatile Organic compounds) NIOSH 8319 3419 Acetone 0SHA 69 3 3 Applicable limit values when using the su				,	,	
Short time value (Workplace exposure limit (EH40/2005)) 3620 m USA (TLV-ACGIH) Acetone Time-weighted average exposure limit 8 h (TLV - Adopted Value) 250 ppi Butane, all isomers Short time value (TLV - Adopted Value) 500 ppi Butane, all isomers Short time value (TLV - Adopted Value) 1000 pr b) National biological limit values If limit values are applicable and available these will be listed below. Germany Aceton (Aceton) Urin: expositionsende, bzw. schichtende 80 mg/l 11/2012 Ständige Senatskom Prüfung gesundheitsschädlich Arbeitsstoffe der DFG USA (BEI-ACGIH) Acetone (Acetone) Urine: end of shift 25 mg/L Casampling methods Product name Test Number Acetone (ketones 1) NIOSH 1300 Acetone (ketones 1) NIOSH 3800 Acetone (ketones 1) NIOSH 2555 Acetone (volatile Organic compounds) NIOSH 2549 Acetone (volatile Organic compounds) Acetone 69 .3 Applicable limit values when using the substance or mixture as intended S0HA 69						1500 ppm
USA (TLV-ACGIH) Acetone Time-weighted average exposure limit 8 h (TLV - Adopted Value) 250 pp Butane, all isomers Short time value (TLV - Adopted Value) 500 pp Butane, all isomers Short time value (TLV - Adopted Value) 1000 pp b) National biological limit values If limit values are applicable and available these will be listed below. 6ermany Aceton (Aceton) Urin: expositionsende, bzw. schichtende 80 mg/l 11/2012 Ständige Senatskom Prüfung gesundheitsschädlich Arbeitsschödlich Arbeitschödlich Arbeitsschödlich Arbeitsschödlich Arbeitschö						3620 mg/r
Acetone Time-weighted average exposure limit 8 h (TLV - Adopted Value) 250 ppi Butane, all isomers Short time value (TLV - Adopted Value) 500 ppi Butane, all isomers Short time value (TLV - Adopted Value) 1000 pr b) National biological limit values If limit values are applicable and available these will be listed below. Germany Aceton (Aceton) Urin: expositionsende, bzw. schichtende 80 mg/l 11/2012 Ständige Senatskom Prüfung gesundheitsschädlich Arbeitsstoffe der DFG USA (BEI-ACGIH) Acetone (Acetone) Urine: end of shift 25 mg/L 25 mg/L Acetone (ketones) Urine: end of shift 25 mg/L Acetone (Acetone) Acetone (ketones 1) Acetone (ketones 1) NIOSH 1300 Acetone (ketones 1) NIOSH 3800 Acetone (ketones 1) NIOSH 2549 Acetone (Volatile Organic compounds) NIOSH 8319 Acetone (Volatile Organic compounds) NIOSH 8319 Acetone 69 3 3 Applicable limit values when using the substance or mixture as intended OSHA 69 53 Publication date: 2016-12-14				·		
Short time value (TLV - Adopted Value) 500 pp Butane, all isomers Short time value (TLV - Adopted Value) 1000 pp b) National biological limit values If limit values are applicable and available these will be listed below. 6ermany Aceton (Aceton) Urin: expositionsende, bzw. schichtende 80 mg/l 11/2012 Ständige Senatskom Prüfung gesundheitsschädlich Arbeitsstoffe der DFG USA (BEI-ACGIH) 25 mg/L 25 mg/L 2 Acetone (Acetone) Urine: end of shift 25 mg/L 2 2 Sampling methods Product name Test Number Acetone (ketones 1) NIOSH 1300 Acetone (ketones 1) Acetone (volatile Organic compounds) NIOSH 2549 Acetone ACETONE and METHYL ETHYL KETONE in urine NIOSH 8319 Acetone Acetone OSHA 69 - - 3 Applicable limit values when using the substance or mixture as intended Fublication date: 2016-12-14 Publication date: 2016-12-14						0.5-
Butane, all isomers Short time value (TLV - Adopted Value) 1000 pr b) National biological limit values If limit values are applicable and available these will be listed below. 6 Germany Aceton (Aceton) Urin: expositionsende, bzw. schichtende 80 mg/l 11/2012 Ständige Senatskom Prüfung gesundheitsschädlich Arbeitsstoffe der DFG USA (BEI-ACGIH) Acetone (Acetone) Urine: end of shift 25 mg/L 2 2 Sampling methods Product name Test Number Acetone (ketones 1) NIOSH 1300 Acetone (ketones 1) NIOSH 2555 Acetone (volatile Organic compounds) NIOSH 2549 Acetone (Volatile Organic compounds) NIOSH 8319 Acetone OSHA 69 3 Applicable limit values when using the substance or mixture as intended Publication date: 2016-12-14	Acetone		0 0	1	Adopted Value)	250 ppm
b) National biological limit values ff limit values are applicable and available these will be listed below. Germany Aceton (Aceton) Urin: expositionsende, bzw. schichtende 80 mg/l 11/2012 Ständige Senatskom Prüfung gesundheitsschädlich Arbeitsstoffe der DFG USA (BEI-ACGIH) Acetone (Acetone) Urine: end of shift 25 mg/L 2 Sampling methods Product name Acetone (ketones 1) Acetone (ketones 1) Acetone (ketones 1) Acetone (ketones 1) Acetone (volatile Organic gases by Extractive FTIR) Acetone (Volatile Organic compounds) ACETONE and METHYL ETHYL KETONE in urine NIOSH Acetone OSHA Acetone OSHA 69 3 Applicable limit values when using the substance or mixture as intended Provision: 3; 5; 15 Publication date: 2016-12-14	D			1 1		500 ppm
If limit values are applicable and available these will be listed below. Germany Aceton (Aceton) Urin: expositionsende, bzw. schichtende 80 mg/l 11/2012 Ständige Senatskom Prüfung gesundheitsschädlich Arbeitsstoffe der DFG USA (BEI-ACGIH) Acetone (Acetone) Urine: end of shift 25 mg/L 2 Sampling methods Product name Test Acetone (ketones 1) NIOSH 1300 Acetone (ketones 1) NIOSH 2555 Acetone (roganic and inorganic gases by Extractive FTIR) NIOSH 3800 Acetone (Volatile Organic compounds) NIOSH 2549 ACETONE and METHYL ETHYL KETONE in urine NIOSH 8319 Acetone OSHA 69 Japplicable limit values when using the substance or mixture as intended	Butane, all isomers		Short time value (TLV - A	dopted Value)		1000 ppm
Aceton (Aceton) Urin: expositionsende, bzw. schichtende 80 mg/l 11/2012 Ständige Senatskom Prüfung gesundheitsschädlich Arbeitsstoffe der DFG USA (BEI-ACGIH) Acetone (Acetone) Urine: end of shift 25 mg/L 2 Sampling methods Product name Test Number Acetone (ketones 1) NIOSH 1300 Acetone (ketones 1) NIOSH 2555 Acetone (organic and inorganic gases by Extractive FTIR) NIOSH 2549 Acetone (Volatile Organic compounds) NIOSH 8319 Acetone OSHA 69 3 Applicable limit values when using the substance or mixture as intended	If limit values are applicable and		elow.			
USA (BEI-ACGIH) Prüfung gesundheitsschädlich Arbeitsstoffe der DFG Acetone (Acetone) Urine: end of shift 25 mg/L .2 Sampling methods Product name Test Number Acetone (ketones 1) NIOSH 1300 Acetone (ketones 1) Acetone (ketones 1) NIOSH 2555 Acetone (organic and inorganic gases by Extractive FTIR) NIOSH 3800 Acetone (Volatile Organic compounds) NIOSH 2549 Acetone G9 Acetone OSHA 69 Japlicable limit values when using the substance or mixture as intended Publication date: 2016-12-14	•	uta . a.u!!!	ha haw achiabtar	80 mm/l	11/2012 6+=	onatolia
USA (BEI-ACGIH) Arbeitsstoffe der DFG Acetone (Acetone) Urine: end of shift 25 mg/L .2 Sampling methods	Aceton (Aceton)	Urin: expositionsend	ie, bzw. schichtende	SU mg/I		
USA (BEI-ACGIH) Acetone (Acetone) Urine: end of shift 25 mg/L .2 Sampling methods						
Acetone (Acetone) Urine: end of shift 25 mg/L 2 Sampling methods Test Number Product name Test Number Acetone (ketones 1) NIOSH 1300 Acetone (ketones 1) NIOSH 2555 Acetone (organic and inorganic gases by Extractive FTIR) NIOSH 3800 Acetone (Volatile Organic compounds) NIOSH 2549 ACETONE and METHYL ETHYL KETONE in urine NIOSH 8319 Acetone OSHA 69 .3 Applicable limit values when using the substance or mixture as intended Publication date: 2016-12-14				1		
Z Sampling methods Product name Test Number Acetone (ketones 1) NIOSH 1300 Acetone (ketones 1) NIOSH 2555 Acetone (organic and inorganic gases by Extractive FTIR) NIOSH 3800 Acetone (Volatile Organic compounds) NIOSH 2549 ACETONE and METHYL ETHYL KETONE in urine NIOSH 8319 Acetone OSHA 69 3 Applicable limit values when using the substance or mixture as intended Publication date: 2016-12-14	UNA (BELACCIU)	Urino: and of chift		25 mg/l		
Product nameTestNumberAcetone (ketones 1)NIOSH1300Acetone (ketones 1)NIOSH2555Acetone (organic and inorganic gases by Extractive FTIR)NIOSH3800Acetone (Volatile Organic compounds)NIOSH2549ACETONE and METHYL ETHYL KETONE in urineNIOSH8319AcetoneOSHA69.3 Applicable limit values when using the substance or mixture as intendedPublication date: 2016-12-14		onne, enu or snill		23 IIIg/L		
Acetone (ketones 1)NIOSH1300Acetone (ketones I)NIOSH2555Acetone (organic and inorganic gases by Extractive FTIR)NIOSH3800Acetone (Volatile Organic compounds)NIOSH2549ACETONE and METHYL ETHYL KETONE in urineNIOSH8319AcetoneOSHA69.3 Applicable limit values when using the substance or mixture as intendedPublication date: 2016-12-14	Acetone (Acetone)			Number		
Acetone (ketones I) NIOSH 2555 Acetone (organic and inorganic gases by Extractive FTIR) NIOSH 3800 Acetone (Volatile Organic compounds) NIOSH 2549 ACETONE and METHYL ETHYL KETONE in urine NIOSH 8319 Acetone OSHA 69 .3 Applicable limit values when using the substance or mixture as intended Publication date: 2016-12-14	Acetone (Acetone) 2 Sampling methods		Test			
Acetone (organic and inorganic gases by Extractive FTIR) NIOSH 3800 Acetone (Volatile Organic compounds) NIOSH 2549 ACETONE and METHYL ETHYL KETONE in urine NIOSH 8319 Acetone OSHA 69 .3 Applicable limit values when using the substance or mixture as intended Publication date: 2016-12-14	Acetone (Acetone) 2 Sampling methods Product name					
Acetone (Volatile Organic compounds) NIOSH 2549 ACETONE and METHYL ETHYL KETONE in urine NIOSH 8319 Acetone OSHA 69 .3 Applicable limit values when using the substance or mixture as intended Publication date: 2016-12-14	Acetone (Acetone) 2 Sampling methods Product name Acetone (ketones 1)		NIOSH	1300		
ACETONE and METHYL ETHYL KETONE in urine NIOSH 8319 Acetone OSHA 69 .3 Applicable limit values when using the substance or mixture as intended revision: 3; 5; 15 Publication date: 2016-12-14	Acetone (Acetone) 2 Sampling methods Product name Acetone (ketones 1) Acetone (ketones I)		NIOSH NIOSH	1300 2555		
Acetone OSHA 69 .3 Applicable limit values when using the substance or mixture as intended Frevision: 3; 5; 15 Publication date: 2016-12-14	Acetone (Acetone) 2 Sampling methods Product name Acetone (ketones 1) Acetone (ketones I) Acetone (organic and inorganic g		NIOSH NIOSH NIOSH	1300 2555 3800		
.3 Applicable limit values when using the substance or mixture as intended r revision: 3; 5; 15 Publication date: 2016-12-14	Acetone (Acetone) 2 Sampling methods Product name Acetone (ketones 1) Acetone (ketones I) Acetone (organic and inorganic g Acetone (Volatile Organic compo	unds)	NIOSH NIOSH NIOSH NIOSH	1300 2555 3800 2549		
revision: 3; 5; 15 Publication date: 2016-12-14	Acetone (Acetone) 2 Sampling methods Product name Acetone (ketones 1) Acetone (ketones I) Acetone (organic and inorganic g Acetone (Volatile Organic compo ACETONE and METHYL ETHYL KET	unds)	NIOSH NIOSH NIOSH NIOSH NIOSH NIOSH	1300 2555 3800 2549 8319		
	Acetone (Acetone) 2 Sampling methods Product name Acetone (ketones 1) Acetone (ketones I) Acetone (organic and inorganic g Acetone (Volatile Organic compo ACETONE and METHYL ETHYL KET Acetone	unds) FONE in urine	NIOSH NIOSH NIOSH NIOSH NIOSH OSHA	1300 2555 3800 2549 8319		
Date of revision: 2019-02-18	Acetone (Acetone) 2 Sampling methods Product name Acetone (ketones 1) Acetone (ketones I) Acetone (organic and inorganic g Acetone (Volatile Organic compo ACETONE and METHYL ETHYL KET Acetone	unds) FONE in urine	NIOSH NIOSH NIOSH NIOSH NIOSH OSHA	1300 2555 3800 2549 8319		
	Acetone (Acetone) 2 Sampling methods Product name Acetone (ketones 1) Acetone (ketones 1) Acetone (organic and inorganic g Acetone (Volatile Organic compo ACETONE and METHYL ETHYL KE Acetone 3 Applicable limit values when u	unds) FONE in urine	NIOSH NIOSH NIOSH NIOSH NIOSH OSHA	1300 2555 3800 2549 8319 69 Publication date:		
	Acetone (Acetone) 2 Sampling methods Product name Acetone (ketones 1) Acetone (ketones 1) Acetone (organic and inorganic g Acetone (Volatile Organic compo ACETONE and METHYL ETHYL KE Acetone 3 Applicable limit values when u	unds) FONE in urine	NIOSH NIOSH NIOSH NIOSH NIOSH OSHA	1300 2555 3800 2549 8319 69 Publication date:		
	Acetone (Acetone) 2 Sampling methods Product name Acetone (ketones 1) Acetone (ketones 1) Acetone (organic and inorganic g Acetone (Volatile Organic compo ACETONE and METHYL ETHYL KE Acetone 3 Applicable limit values when u	unds) FONE in urine	NIOSH NIOSH NIOSH NIOSH NIOSH OSHA	1300 2555 3800 2549 8319 69 Publication date:	2019-02-18	

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

DNEL/DMEL - Workers

acetone	acetone									
Effect level (DNEL/DMEL)	Туре	Value	Remark							
DNEL	Long-term systemic effects inhalation	1210 mg/m³								
	Acute local effects inhalation	2420 mg/m ³								
	Long-term systemic effects dermal	186 mg/kg bw/day								
DNEL/DMEL Constal nonulation										

DNEL/DMEL - General population acetone

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	200 mg/m³	
	Long-term systemic effects dermal	62 mg/kg bw/day	
	Long-term systemic effects oral	62 mg/kg bw/day	

PNEC acetone

Compartments	Value	Remark
Fresh water	10.6 mg/l	
Aqua (intermittent releases)	21 mg/l	
Marine water	1.06 mg/l	
STP	100 mg/l	
Fresh water sediment	30.4 mg/kg sediment dw	
Marine water sediment	3.04 mg/kg sediment dw	
Soil	29.5 mg/kg soil dw	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type AX at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN374).

c) Eye protection:

Protective goggles.

d) Skin protection:

Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Acetone odour
Odour threshold	No data available
Colour	Colourless
Particle size	No data available
Explosion limits	1.8 - 13 vol %
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	Not applicable
Boiling point	Not applicable
Evaporation rate	No data available
Relative vapour density	No data available
Vapour pressure	8530 hPa ; 20 °C
Solubility	Water ; complete
	Ethanol ; soluble
	Ether ; soluble
Relative density	No data available
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Flash point	Not applicable

Publication date: 2016-12-14 Date of revision: 2019-02-18

Revision number: 0001

Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
рН	No data available

9.2. Other information Absolute density

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

Oxidizing agents, (strong) acids, (strong) bases.

10.6. Hazardous decomposition products

Upon combustion: CO and CO2 are formed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

PUR CLEANER

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark		
						determination			
Oral	LD50		> 5000 mg/kg bw		Rat	Calculated value			
Judgement is based on the relevant ingredients									

acetone

Route of exposure	Parameter	Method	Value	Exposure time			Remark
						determination	
Oral	LD50	Equivalent to OECD 401	5800 mg/kg		Rat (female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	20000 mg/kg		Rabbit (male)	Experimental value	
Inhalation (vapours)	LC50	Other	76 mg/l	4 h	Rat (female)	Experimental value	

Conclusion Not classified for acute toxicity

Corrosion/irritation

PUR CLEANER

No (test)data on the mixture available

Classification is based on the relevant ingredients

<u>acetone</u>

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Еуе	Irritating	OECD 405		24; 48; 72 hours	Rabbit	Weight of evidence	
Skin	Not irritating	Other	3 day(s)	24; 48; 72 hours	Guinea pig	Weight of evidence	
Inhalation	Slightly irritating	Human observation study	20 minutes		Human	Literature	

Conclusion

Causes serious eye irritation.

Not classified as irritating to the skin

Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

PUR CLEANER

Reason for revision: 3; 5; 15

Publication date: 2016-12-14 Date of revision: 2019-02-18

No (test)data on the mixture available

Judgement is based on the relevant ingredients acetone

Route of exposure	Result	Method	 Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Human observation		Human	Literature	

Conclusion

Not classified as sensitizing for skin

Not classified as sensitizing for inhalation

Specific target organ toxicity

PUR CLEANER

No (test)data on the mixture available

Classification is based on the relevant ingredients $\underline{acetone}$

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral	NOAEL	Equivalent to OECD 408	20 mg/l		No effect	13 week(s)	Mouse (male / female)	Experimental value
Dermal								Not relevant, expert judgement
Inhalation (vapours)	NOAEC	Other	19000 ppm		No effect	8 week(s)	Rat (male)	Literature
Inhalation (vapours)	Dose level	Human observation study	361 ppm	Central nervous system	neurotoxic effects	2 day(s)	Human	Epidemiological study

Conclusion

May cause drowsiness or dizziness. Not classified for subchronic toxicity

Mutagenicity (in vitro)

PUR CLEANER

No (test)data on the mixture available

ace	tone				
	Result	Method	Test substrate	Effect	Value determination
	Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value

Mutagenicity (in vivo)

PUR CLEANER

No (test)data on the mixture available

Judgement is based on the relevant ingredients

<u>acetone</u>

R	Result	Method	Exposure time	Test substrate	Organ	Value determination
٦	Negative		13 week(s)	Mouse (male / female)		Literature

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

PUR CLEANER

No (test)data on the mixture available

Judgement is based on the relevant ingredients

acetone

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	- 0.	Value determination
Dermal	NOEL	Other	79 mg	51 week(s)	Mouse (female)	No effect		Literature

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

PUR CLEANER

No (test)data on the mixture available Judgement is based on the relevant ingredients

acetone

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEC	Equivalent to OECD 414	11000 ppm	6 days (gestation, daily) - 19 days (gestation, daily)	Rat (male / female)			Experimental value
Effects on fertility	NOAEL	Other	900 mg/kg bw/day	13 week(s)	Rat (male)	No effect		Literature

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

PUR CLEANER

No (test)data on the mixture available

Judgement is based on the relevant ingredients

acetone

Parameter	Method	Value	Organ	Effect	Exposure time	 Value determination
			Skin	Skin dryness or cracking		Literature study

Conclusion

Repeated exposure may cause skin dryness or cracking.

Chronic effects from short and long-term exposure

PUR CLEANER

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin. Skin rash/inflammation. Dry/sore throat. Headache. Nausea. Feeling of weakness. Loss of weight. Possible inflammation of the respiratory tract.

SECTION 12: Ecological information

12.1. Toxicity

PUR CLEANER

No (test)data on the mixture available

Judgement is based on the relevant ingredients

<u>acetone</u>

	Parameter	Method	Value	Duration	Species	0	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	EU Method C.1	5540 mg/l	96 h	Salmo gairdneri	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	LC50	Other	12600 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	EC50		> 7000 mg/l	96 h	Selenastrum capricornutum	Static system	Fresh water	Experimental value; Nominal concentration
Long-term toxicity aquatic crustacea	NOEC	Equivalent to OECD 211	2212 mg/l	28 day(s)	Daphnia magna	Flow- through system	Fresh water	Experimental value

Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

acetone

В	iodegradation water			
	Method	Value	Duration	Value determination
	OECD 301B: CO2 Evolution Test	90.9 %	28 day(s)	Experimental value

Conclusion

Contains readily biodegradable component(s)

12.3. Bioaccumulative potential

PUR CLEANER

Log	Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

<u>acetone</u>

BCF fishes								
Parameter	Method		Value	Duration	Species			Value determination
BCF			0.69		Pisces			
BCF other aquatic o	organisms							
Parameter	Method		Value	Duration	Species			Value determination
BCF	BCFWIN		3					Calculated value
Log Kow								
Method		Remark		Value		Temperature	Va	lue determination
				-0.24			Tes	st data

Conclusion

Does not contain bioaccumulative component(s)

12.4. Mobility in soil

No (test)data on mobility of the components available

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Other adverse effects

PUR CLEANER

Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardoucius

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997. Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

16 05 04* (gases in pressure containers and discarded chemicals: gases in pressure containers (including halons) containing hazardous substances). 20 01 29* (separately collected fractions (except 15 01): detergents containing hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Refer to manufacturer/supplier for information on recovery/ recycling. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Specific treatment. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

UN number	1950	
14.2. UN proper shipping name	÷	
Proper shipping name	Aerosols	
14.3. Transport hazard class(es)		
Hazard identification number		
Class	2	
Classification code	5F	
14.4. Packing group		
Packing group		
Labels	2.1	
14.5. Environmental hazards		
Environmentally hazardous substance mark	no	
14.6. Special precautions for user		
Special provisions	190	
Special provisions	327	
Special provisions	344	
Special provisions	625	

Reason for revision: 3; 5; 15

Publication date: 2016-12-14 Date of revision: 2019-02-18

Limited quantities Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Rail (RID)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Hazard identification number	23
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
4.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Inland waterways (ADN)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Sea (IMDG/IMSBC)

UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Marine pollutant	-
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	63
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7. Transport in bulk according to Annex II of Marpol and the	e IBC Code
Annex II of MARPOL 73/78	Not applicable
n for revision: 3; 5; 15	Publication date: 2016-12-14
	Date of revision: 2019-02-18

Air (ICAO-TI/IATA-DGR)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	30 kg G

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

	VOC content	Remark	
1	99.2 % - 100 %		ļ

Ingredients according to Regulation (EC) No 648/2004 and amendments

≥30% aliphatic hydrocarbons

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	substances or of the mixture	
acetone	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class4.1; (d) hazard class5.1.	 Shall not be used in: ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, tricks and jokes, games for one or more participants, or any article intended to be used as such, even w ornamental aspects, Articles not complying with paragraph 1 shall not be placed on the market. Shall not be placed on the market if they contain a colouring agent, unless required fo fiscal reasons, or perfume, or both, if they:
acetone	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category	 Shall not be used, as substance or as mixtures in aerosol dispensers where these aeros dispensers are intended for supply to the general public for entertainment and decorativ purposes such as the following: metallic glitter intended mainly for decoration, artificial snow and frost,
son for revision: 3; 5; 15		Publication date: 2016-12-14
		Date of revision: 2019-02-18

DIID CIEANED

	PUR CL	
	1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	 "whoopee" cushions, silly string aerosols, imitation excrement, horns for parties, decorative flakes and foams, artificial cobwebs, stink bombs. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: "For professional users only". By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
<u>National legislation Belgium</u> <u>PUR CLEANER</u> No data available		
National legislation The Netherlar	<u>ids</u>	
PUR CLEANER Waterbezwaarlijkheid	Z (2); Algemene Beoordelingsmethodiek	(ABM)
<u>National legislation France</u> <u>PUR CLEANER</u> No data available <u>National legislation Germany</u>		
PUR CLEANER WGK	1; Verordnung über Anlagen zum Umga	ng mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
acetone		
TA-Luft TRGS900 - Risiko der Fruchtschädigung	5.2.5 Aceton; Y; Risiko der Fruchtschädigung b Grenzwertes nicht befürchtet zu werder	oraucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen n
PUR CLEANER No data available <u>acetone</u> TLV - Carcinogen L5.2. Chemical safety assessment No chemical safety assessment	Acetone; A4 eent has been conducted for the mixture.	
TION 16: Other infor		
Full text of any H-statements refe H220 Extremely flammable gas H222 Extremely flammable aer H225 Highly flammable liquid a H229 Pressurised container: M H280 Contains gas under press H319 Causes serious eye irritat H336 May cause drowsiness or	r red to under heading 3: osol. Ind vapour. ay burst if heated. ure; may explode if heated. ion. dizziness.	
ADI Accept AOEL Accept CLP (EU-GHS) Classif DMEL Derive EC50 Effect ErC50 EC50 i LC50 Lethal LD50 Lethal NOAEL No Ob NOEC No Ob OECD Organi PBT Persist PNEC Predict	JAL CLASSIFICATION BY BIG able daily intake able operator exposure level cation, labelling and packaging (Globally Har d Minimal Effect Level d No Effect Level Concentration 50 % n terms of reduction of growth rate Concentration 50 % Dose 50 % Served Adverse Effect Level served Adverse Effect Level served Effect Concentration sation for Economic Co-operation and Devel ent, Bioaccumulative & Toxic ted No Effect Concentration Treatment Process	
on for revision: 3; 5; 15		Publication date: 2016-12-14 Date of revision: 2019-02-18

very Persistent & very Bioaccumulative

vPvB

The informati on in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructi ons in this safety data sheet does not release the user from the obligati on to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limit in g conditi ons as stated in your BIG licence agreement or when this is failing the general conditi ons of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3; 5; 15

Publication date: 2016-12-14 Date of revision: 2019-02-18

Revision number: 0001