Technical Data Sheet Internal Adjustable Louvre Grille

Product



Use

• To cover the inner opening on the cavity sleeve and provide an aesthetically acceptable appearance, while maintaining a free air flow.

INSTALLATION

- Internal grilles should be positioned over the internal opening of the cavity sleeve and fixed to the wall using screws and wall plugs
- Never block or restrict the flow of air through these ventilators
- Do not use hit & miss grilles when ventilating a gas or heat producing appliance
- We recommend using our external cowls to help reduce draughts caused by wind blast

FEATURES & BENEFITS

- Adjustable background ventilators for rooms
- Aesthetically pleasing
- Integral Flyscreen with concealed fixings
- Louvre face and low profile vent
- UV stable
- Suitable for new build or Retro-fit
- Not suitable for boilers, stoves ad fires.
- Easy installation
- Mechanically fixed
- Durable and resistant to decay
- Complies with relevant Building Regulations & British Standards

Product Details

9x3 Adjustable Louvre vent	
Size	260(L) x 104mm (H)
Ventilation Free Area	4325mm ² 43cm ²
Colour	White
Code	IAL93

9x6 Adjustable Louvre vent		
Size	260(L) x 170mm (H)	
Ventilation Free Area	7250mm ² 72cm ²	
Colour	White	
Code	IAL96	

9x9 Adjustable Louvre vent	
Size	260(L) x 260mm (H)
Ventilation Free Area	8225mm ² 82cm ²
Colour	White
Code	IAL99

