

Description	Value
<b>General information:</b>	
Product name:	ALPHA1 L 25-65 130
Product No:	<a href="#">99199582</a>
EAN number:	5712608550225
<b>Technical:</b>	
Rated flow:	1.94 m <sup>3</sup> /h
Rated head:	3.28 m
Maximum head:	65 dm
TF class:	95
Approvals:	CE, VDE, EAC
Model:	C
<b>Materials:</b>	
Pump housing:	Cast iron
Pump housing:	EN 1561 EN-GJL-150
Pump housing:	ASTM A48-150B
Impeller:	Composite
Impeller:	PES+30% GF
<b>Installation:</b>	
Range of ambient temperature:	0 .. 55 °C
Maximum operating pressure:	10 bar
Type of connection:	G
Size of connection:	1 1/2 inch
Pressure rating for connection:	PN 10
Port-to-port length:	130 mm
<b>Liquid:</b>	
Pumped liquid:	Water
Liquid temperature range:	2 .. 95 °C
Selected liquid temperature:	60 °C
Density:	983.2 kg/m <sup>3</sup>
<b>Electrical data:</b>	
Minimum power input - P1:	4 W
Power input P1:	60 W
Mains frequency:	50 / 60 Hz
Rated voltage:	1 x 230 V
Maximum current consumption:	0.05 .. 0.52 A
Enclosure class (IEC 34-5):	X4D
Insulation class (IEC 85):	F
Built-in motor protection:	NONE
Thermal protec:	ELEC
<b>Others:</b>	
Energy (EEL):	0.20
Terminal box position:	9H
Net weight:	1.95 kg
Gross weight:	2.08 kg
Shipping volume:	0.004 m <sup>3</sup>
Sales region:	GB

