

Description	Value
<b>General information:</b>	
Product name:	SOLOLIFT2 CWC-3
Product No:	97775331
EAN number:	5710624187401
<b>Technical:</b>	
Pump speed on which pump data are based:	2800 rpm
Rated flow:	1.32 l/s
Maximum flow:	2.28 l/s
Rated head:	5.88 m
Maximum head:	8.5 m
Type of impeller:	VORTEX with GRINDER
Max. Particle:	25 mm
Approvals:	CE, VDE, CHROHS, MORO, UKCA, WATERMARK
Curve tolerance:	ISO9906:2012 3B
<b>Materials:</b>	
Pump housing:	Composite
Impeller:	Polymer - PPE
Tank:	Plastic
Tank:	PP
<b>Installation:</b>	
Range of ambient temperature:	0 .. 40 °C
Type of inlet connection:	Smooth pipe
Type of outlet connection:	Smooth pipe
Size of inlet connection:	32/36/40, 36/40/50, DN 100
Size of outlet connection:	22/25/28/32/36/40
Pressure rating for connection:	PN 1,5
Number of leads:	3X0,75MM2
<b>Liquid:</b>	
Liquid temperature range:	0 .. 50 °C
Density:	998.2 kg/m <sup>3</sup>
<b>Electrical data:</b>	
Power input P1:	620 W
Rated power - P2:	0.42 kW
Mains frequency:	50 Hz
Rated voltage:	1 x 220-240 V
Rated current:	3 A
Cos phi - power factor:	0.92
Number of poles:	2
Enclosure class (IEC 34-5):	IP44
Insulation class (IEC 85):	F
Thermal protec:	THERMIK S06-150-05
Length of power cable:	1.2 m
Cable type:	H05VV-F-3G
Power plug:	without
<b>Tank:</b>	
Tank volume nominal:	9 l
<b>Others:</b>	
Net weight:	8.1 kg
Gross weight:	9.69 kg
Shipping volume:	0.045 m <sup>3</sup>
Sales region:	Australia
Environmental approvals:	WEEE

