

Description	Value
General information:	
Product name:	SOLOLIFT2 C-3
Product No:	97775332
EAN number:	5710624187418
Technical:	
Pump speed on which pump data are based:	2800 rpm
Rated flow:	1.7 l/s
Maximum flow:	3.4 l/s
Rated head:	5.95 m
Maximum head:	8.5 m
Type of impeller:	VORTEX
Max. Particle:	10 mm
Approvals:	CE,VDE,CHROHS,MORO,UKCA, WATERMARK
Curve tolerance:	ISO9906:2012 3B
Materials:	
Pump housing:	Composite
Impeller:	Polymer - PA
Tank:	Plastic
Tank:	PP
Installation:	
Range of ambient temperature:	0 .. 40 °C
Type of inlet connection:	Smooth pipe
Type of outlet connection:	Smooth pipe
Size of inlet connection:	32/36/40, 36/40/50
Size of outlet connection:	22/25/28/32/36/40
Pressure rating for connection:	PN 1,5
Number of leads:	3X0,75MM2
Liquid:	
Liquid temperature range:	0 .. 75 °C
Density:	998.2 kg/m ³
Electrical data:	
Power input P1:	640 W
Rated power - P2:	0.42 kW
Mains frequency:	50 Hz
Rated voltage:	1 x 220-240 V
Rated current:	3.1 A
Cos phi - power factor:	0.9
Number of poles:	2
Enclosure class (IEC 34-5):	IP44
Insulation class (IEC 85):	F
Thermal protec:	THERMIK S06-140-05
Length of power cable:	1.2 m
Cable type:	H05VV-F-3G
Power plug:	without
Tank:	
Tank volume nominal:	6 l
Others:	
Net weight:	7.25 kg
Gross weight:	8.8 kg
Shipping volume:	0.036 m ³
Sales region:	Australia
Environmental approvals:	WEEE

