

thermostats



altecnic
Caleffi group

thermostats



Altecnic are able to offer a range of thermostats for a variety of applications.

room thermostats

Prod Code	Description
IM-100077	240V SP 5/30°C, room stat
IM-TA2/544819	240V frost stat, tamper proof cover

Technical Specification	Room	Frost
Temperature range:	7 to 30°C	5±1°C fixed
Temperature differential:	≤1°C	≤1°C
Max. body temperature:	50°C	50°C
Contact rating:	16<2.5>A/250V~	6<2.5>A/250V~
Protection:	IP 20	IP 30
Temperature rate of change:	1°C/15min	1°C/15min

surface contact thermostats

Prod Code	Description
IM-BRC/54830	20°C/90°C 240V cylinder/pipe thermostat grey

Technical Specification	
Temperature range:	20 to 90°C
Temperature differential:	8±3°C
Max. body temperature:	80°C
Contact rating:	15<2.5>A/250V~
Temperature rate of change:	1°C/min
Protection:	IP 20

immersion thermostat - 1/2" pocket adjustable

Prod Code	Description
IM-TC2/542470	0°C/90°C adjustable 100mm stem SPDT grey

Technical Specification	
Switching point:	0 ± 5 / 90 ± 3 °C
Temperature differential:	4±1°C
Max. body temperature:	80°C
Max. bulb temperature:	125°C
Protection:	IP 40
Contact rating:	10<2.5>A/250V~ 6<2.6>A/250V~

dual immersion thermostat - 1/2" pocket x 120mm stem

Prod Code	Description
IM-TLSC/542816	60°C/90°C adjustable limit / manual reset grey

Technical Specification	
Adjustment range:	60 / 90 ± 3 °C
Temperature differential:	8±2°C
Max. temperature limit:	90 / 110 ± 0.5 °C
Max. head temperature:	80°C
Max. bulb temperature:	150°C
Protection:	IP 40
Contact rating:	10<2.5>A/250V~ 7A/380V~

For more information and details of the full range of thermostats please contact Altecnic, see contact details below.

E & O.E
© Altecnic Ltd. 2017

Altecnic Ltd Mustang Drive, Stafford, Staffordshire ST16 1GW
T: +44 (0)1785 218200 E: sales@altecnic.co.uk
Registered in England No: 2095101

altecnic.co.uk

AL 081 08-02-2019

altecnic
Caleffi group