

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

## EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM SILVER GREY

Supercedes Date: 02-Mar-2018

Revision Date 15-Mar-2016

**Revision Number** 1

# Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

## 1.1. Product Identifier

Product Name	EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM SILVER GREY
Pure substance/mixture	Mixture

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Cement. Building and construction work.
Uses advised against	None known

1.3. Details of the supplier of the safety data sheet

Company Name Bostik Industries Limited Newtown, Swords Co. Dublin Ireland Tel: +353 (1) 8624900

Fax: +353 (1) 8402186

E-mail address

SDS.box-EU@bostik.com

## 1.4. Emergency telephone number

United Kingdom	+44 (1785) 272650
Ireland	+353 (1) 8624900 (Monday- Friday 9am-5pm)

## Section 2: HAZARD IDENTIFICATION

## 2.1. Classification of the substance or mixture

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Corrosion/Irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Skin sensitisation	Category 1 - (H317)
Specific target organ toxicity (single exposure)	Category 3 - (H335)

## 2.2. Label Elements

## Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains Cement Portland White



Signal Word DANGER

EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM SILVER GREY Supercedes Date: 02-Mar-2018 Revision Date 15-Mar-2016

**Revision Number** 1

## Hazard statements

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

### Precautionary Statements - EU (§28, 1272/2008)

P102 - Keep out of reach of children

P261 - Avoid breathing dust

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P271 - Use only outdoors or in a well-ventilated area

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P315 - Get immediate medical advice/attention

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P361 + P364 - Take off immediately all contaminated clothing and wash it before reuse

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P501 - Dispose of contents/containers in accordance with local regulations

#### Additional information

Chromium VI reduced (according to Regulation (EC) 1907/2006 - Annex XVII)

Cement product for which the amount of chromium VI was decreased to < 0,0002 % by a reduction agent (related to the total dry weight)

## 2.3. Other Hazards

## **General Hazards**

Product dust may be irritating to eyes, skin and respiratory system. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease.

## PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.1 Substances

Mixture

## 3.2 Mixtures

Chemical Name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Cement Portland White	266-043-4	65997-15-1	>25 - <40	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318)		Exempt
Calcium sulfate	231-900-3	7778-18-9	1 - <5	^		01-2119444918-26 -XXXX
Aluminum oxide (Al2O3)	215-691-6	1344-28-1	1 - <5	^		01-2119529248-35 -XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classifed, however, the substance is listed in section 3 as it has an OEL.

#### EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM SILVER GREY Supercedes Date: 02-Mar-2018

Revision Date 15-Mar-2016

**Revision Number** 1

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## Section 4: FIRST AID MEASURES

## 4.1. Description of first aid measures

General Advice	If symptoms persist, call a doctor.	
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.	
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a doctor. Brush off loose particles from skin.	
Eye contact	If symptoms persist, call a doctor. In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.	
Ingestion	Do NOT induce vomiting. Rinse mouth. If swallowed, seek medical advice immediately and show this container or label.	
Self-Protection of the First Aider	Use personal protective equipment as required.	
4.2. Most important symptoms and	d effects, both acute and delayed	
Symptoms	None known.	
4.3. Indication of any immediate medical attention and special treatment needed		

Note to doctors

May cause sensitisation of susceptible persons. Treat symptomatically.

## Section 5: FIRE-FIGHTING MEASURES

## 5.1. Extinguishing media

## Suitable Extinguishing Media

Use extinguishing agent suitable for type of surrounding fire.

## Unsuitable Extinguishing Media

None known

## 5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating and toxic gases and vapours.

## Hazardous Combustion Products Carbon oxides.

## 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit.

## Section 6: ACCIDENTAL RELEASE MEASURES

## 6.1. Personal precautions, protective equipment and emergency procedures

## **Personal Precautions**

Avoid creating dust. Do not get in eyes, on skin, or on clothing. Wear protective gloves/protective clothing and eye/face protection.

## For emergency responders

Sweep up to prevent slipping hazard.

EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM SILVER GREY Supercedes Date: 02-Mar-2018 Revision Date 15-Mar-2016

Revision Number 1

## 6.2. Environmental precautions

Prevent entry into waterways, sewers, basements or confined areas. Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

Methods for Containment Prevent dust cloud. Take up mechanically, placing in appropriate containers for disposal.

Methods for cleaning up Avoid creating dust. Sweep up and shovel into suitable containers for disposal.

## 6.4. Reference to other sections

Reference to other sections Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION Section 13: DISPOSAL CONSIDERATIONS

## Section 7: HANDLING AND STORAGE

## 7.1. Precautions for safe handling

#### Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid generation of dust. Avoid contact with skin and eyes. Wash contaminated clothing before reuse.

#### **General Hygiene Considerations**

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Regular cleaning of equipment, work area and clothing is recommended.

## 7.2. Conditions for safe storage, including any incompatibilities

#### **Storage Conditions**

Keep out of the reach of children. Protect from direct contact with water or excessive moisture. Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

## 7.3. Specific end use(s)

## Other Information

Recommendation(s). Observe technical data sheet.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1. Control parameters

Chemical Name	European Union	Ireland	United Kingdom
Cement Portland White	-	TWA: 1 mg/m <sup>3</sup>	STEL: 30 mg/m <sup>3</sup>
65997-15-1		STEL: 3 mg/m <sup>3</sup>	STEL: 12 mg/m <sup>3</sup>
			TWA: 10 mg/m <sup>3</sup> (inhalable)
			TWA: 4 mg/m <sup>3</sup> (respirable)
Calcium sulfate	-	TWA: 10 mg/m <sup>3</sup>	-
7778-18-9		STEL: 30 mg/m <sup>3</sup>	
Aluminum oxide (Al2O3)	-	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> inhalable dust
1344-28-1		TWA: 4 mg/m <sup>3</sup>	TWA: 4 mg/m <sup>3</sup> respirable dust
		STEL: 30 mg/m <sup>3</sup>	
		STEL: 12 mg/m <sup>3</sup>	

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration No information available. (PNEC)

## 8.2. Exposure controls

United Kingdom, Ireland - BE

## EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM SILVER GREY Supercedes Date: 02-Mar-2018

Revision Date 15-Mar-2016

**Revision Number** 1

Engineering Controls	Ensure adequate ventilation, especially in confined areas.
Personal Protective Equipment	t
Eye/Face Protection	Tight sealing safety goggles. Face protection shield. Wear safety glasses with side shields (or goggles).
Hand Protection	For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn. Gloves made of plastic or rubber. Gloves should be replaced regularly and if there is any sign of damage to the glove material.
Skin and Body Protection	Suitable protective clothing. Gloves made of plastic or rubber. Avoid contact with skin, eyes or clothing. Wear appropriate personal protective clothing to prevent skin contact.
Respiratory Protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. Avoid generation of dust.
Recommended filter type:	Particle filter device (DIN EN 143).

Environmental Exposure Controls Do not allow into any sewer, on the ground or into any body of water.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

## 9.1. Information on basic physical and chemical properties

Solid Powder Silver Grey Slight No information available	
<u>Values</u> No information available No information available No information available No information available	<u>Re</u>
No information available No information available	
No information available No information available No information available No information available No information available Cement based products react and	
No information available No information available	
No information available No information available No information available No information available 100 No data available	
	Powder Silver Grey Slight No information available <u>Values</u> No information available No information available

emarks • Method

EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM SILVER GREY Supercedes Date: 02-Mar-2018 Revision Date 15-Mar-2016

**Revision Number** 1

Bulk Density VOC content (%) No data available

## Section 10: STABILITY AND REACTIVITY

## 10.1. Reactivity

None under normal use conditions.

## 10.2. Chemical stability

Stable under normal conditions.

Explosion Data Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

#### 10.3. Possibility of hazardous reactions

Possibility of Hazardous Reactions None under normal processing.

## 10.4. Conditions to avoid

Heat, flames and sparks.

#### 10.5. Incompatible materials

No information available.

## 10.6. Hazardous decomposition products

None under normal use conditions.

## Section 11: TOXICOLOGY INFORMATION

## 11.1. Information on toxicological effects

## Information on likely routes of exposure

#### **Product Information**

No information or data specific to the product on this toxicological (health) effect is available.

Inhalation	Inhalation of dust in high concentration may cause irritation of respiratory system.
Eye contact	Severely irritating to eyes. Dust contact with the eyes can lead to mechanical irritation.
Skin Contact	When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.
Ingestion	Based on available data, the classification criteria are not met.
Sensitisation	Cement product for which the amount of chromium VI was decreased to < 0,0002 % by a reduction agent (related to the total dry weight).

## Delayed and immediate effects as well as chronic effects from short and long-term exposure\_

Skin Corrosion/Irritation	When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.
Serious eye damage/eye irritation	Risk of serious damage to eyes.

## EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM SILVER GREY Supercedes Date: 02-Mar-2018

Revision Date 15-Mar-2016

**Revision Number** 1

Sensitisation	May cause sensitisation of susceptible persons. Cement product for which the amount of chromium VI was decreased to < 0,0002 % by a reduction agent (related to the total dry weight).
Germ Cell Mutagenicity	Not applicable.
Carcinogenicity	Not applicable.
Reproductive Toxicity	No information available.
STOT - Single Exposure	May cause disorder and damage to the. Respiratory system.
STOT - Repeated Exposure	No information available.
Target Organ Effects	Eyes, Respiratory system, Skin.
Aspiration hazard	No information available.
Numerical measures of toxicity	
Acute Toxicity	
Component Information	
Toxicity Data	Data obtained on the component(s) include

## Section 12: ECOLOGICAL INFORMATION

## 12.1. Toxicity

Ecotoxicity

No information available

#### <u>Component Information</u> Data obtained on the component(s) include

Chemical Name	Algae/aquatic plants	Fish	Crustacea	M-Factor
Calcium sulfate	CL50 (72h) >100 mg/L Algae	LC50 96 h > 1970 mg/L	CE50 (48h) >100 mg/L	
7778-18-9		(Pimephales promelas static)	Waterflea (Daphnia magna)	
		LC50 96 h = 2980 mg/L		
		(Lepomis macrochirus static)		

## 12.2. Persistence and degradability

No information available.

## 12.3. Bioaccumulative potential

No information available.

Partition coefficient

No information available

## 12.4. Mobility in soil

Mobility in soil No information available.

## 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM SILVER GREY Supercedes Date: 02-Mar-2018 Revision Date 15-Mar-2016

**Revision Number** 1

## 12.6. Other adverse effects

No information available

#### **Endocrine Disruptor Information**

This product does not contain any known or suspected endocrine disruptors.

## Section 13: DISPOSAL CONSIDERATIONS

#### 13.1. Waste treatment methods

Waste from Residues/Unused Products	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Improper disposal or reuse of this container may be dangerous and illegal.
European Waste Catalogue	17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03
Other Information	Waste codes should be assigned by the user based on the application for which the product was used.

## Section 14: TRANSPORTATION INFORMATION

<u>ADR</u>

14.1UN/ID no14.2Proper Shipping Name14.3Transport hazard class(es)14.4Packing Group	Not regulated Not regulated Not regulated Not regulated		
14.5 Environmental Hazard	Not applicable		
14.6 Special Provisions	None		
IMDG			
14.1 UN Number	Not regulated		
14.2 Proper Shipping Name	Not regulated		
14.3 Transport hazard class(es)	Not regulated		
14.4 Packing Group	Not regulated		
14.5 Marine Pollutant	Np		
14.6 Special Provisions	None		
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available			
<u>RID</u>			
14.1 UN Number	Not regulated		
14.2 Proper Shipping Name	Not regulated		
14.3 Transport hazard class(es)	Not regulated		
14.4 Packing Group	Not regulated		
14.5 Environmental Hazard	Not applicable None		
14.6 Special Provisions	None		
ICAO (air)			
14.1 UN/ID no	Not regulated		
14.2 Proper Shipping Name	Not regulated		
14.3 Hazard Class	Not regulated		
14.4 Packing Group	Not regulated		
14.5 Environmental Hazard	Not applicable		
14.6 Special Provisions	None		
•			

## IATA

EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM SILVER GREY Supercedes Date: 02-Mar-2018

#### Revision Date 15-Mar-2016

Revision Number 1

14.1 UN/ID no	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing Group	Not regulated
14.5 Environmental Hazard	Not applicable
14.6 Special Provisions	None

## Section 15: REGULATORY INFORMATION

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

## Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

## EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

## EU-REACH (1907/2006) - Annex XIV - List of substances subject to Authorization

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

Persistent Organic Pollutants Not applicable

#### 15.2. Chemical safety assessment

None

## Section 16: OTHER INFORMATION

#### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H335 - May cause respiratory irritation

H315 - Causes skin irritation

H318 - Causes serious eye damage

EVO-STIK TECHNIK TGS TOTAL GROUT SYSTEM SILVER GREY Supercedes Date: 02-Mar-2018

Legend

SVHC: Substances of Very High Concern for Authorisation:

LegendSection 8: Exposure controls and personal protectionTWATWA (time-weighted average)STELCeilingMaximum limit value\*PBTPersistent, Bioaccumulative, and Toxic (PBT) ChemicalsSTOT (RE):STOT (RE):Specific target organ toxicity - Repeated exposureSTOT (SE):Specific target organ toxicity - Single exposureEWC:European Waste Catalogue

Key literature references and sources for data

Classification and labeling data calculated from data received from raw material suppliers

ed By Product Safety & Regulatory Affairs			
15-Mar-2016			
Indication of changes			
Not applicable.			
No information available			
No information available			

## This safety data sheet complies with the requirements of: Regulation (EC) No. 1907/2006

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

United Kingdom, Ireland - BE

Revision Date 15-Mar-2016

STEL (Short Term Exposure Limit)

Skin designation