



GALVATEC ZINCSPRAY

FAST DRYING ZINC COATING



TECHNICAL SPECIFICATIONS

Chemical base:	Zinc powder in solvent mixture
Colour:	Light grey
Maximum temperature resistance:	120 °C
Minimum temperature resistance:	-30 °C

STORAGE CONDITIONS

At least 24 months after date of manufacture.

Close the container properly and store in a dry, cool and frost-free location.

PRODUCT DESCRIPTION

Fast drying zinc coating.

FIELD OF APPLICATION

For protecting (cold galvanizing) of metal against rust and corrosion, such as bodywork, welding seams, fences, gutter brackets and stairs. Also to repair damage to previously galvanised metal.

PROPERTIES

- Rust and corrosion resistant
- Quick-drying
- Electrically conductive
- Resistant to temperatures between -30°C to +120°C
- Contains 98% pure zinc
- Paintable

PREPARATION

Preliminary Surface Treatment: Make sure that the surface is clean, dry, and free of grease. Remove rust, mill scale and loose coatings.

APPLICATION

Directions for use:

Spray surface evenly and thinly from a distance of approx. 30 cm. It is better to apply several thin coatings than one thick coating. Apply the next layer within 10 minutes or 24 hours after the previous layer. Regularly shake during use. After use, hold the can upside down and spray until only propellant gas is released.

Stains/residue: Remove wet stains with thinner. Remove dry stains with paint stripper.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.