

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.08.2022 Version number 31 (replaces version 30) Revision: 18.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: GRF GALVATEC ZINCSPRAY AE 400ML*12 L222
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Metal-working product
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Bison International

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: Bison QESH
- · 1.4 Emergency telephone number:

National Poisons Information Centre: +353 (1) 809 2166 (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

- IE-EN

www.griffon.eu 1/12



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.08.2022 Version number 31 (replaces version 30) Revision: 18.08.2022

Trade name: GRF GALVATEC ZINCSPRAY AE 400ML*12 L222

(Contd. of page 1)

- IF-FN

Hazard pictograms







GHS02 GHS07 GHS09

· Signal word Danger

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with national regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Metal working product

Dangerous components:		
CAS: 7440-66-6 EINECS: 231-175-3 Index number: 030-001-01-9	zinc powder -zinc dust (stabilized) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49- XXXX	acetone Flam. Liq. 2, H225; UEye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	n-Butan Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-25%
	(C	ontd. on page

www.griffon.eu 2/12



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.08.2022 Version number 31 (replaces version 30) Revision: 18.08.2022

Trade name: GRF GALVATEC ZINCSPRAY AE 400ML*12 L222

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	contd. of page 2) 10-25%		
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane	10-25%		
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35- XXXX	ethylbenzene Tox. 1, H304; Acute Tox. 4, H332	≥2.5-<10%		
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane The Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-2.5%		
Additional information: For the wording of the listed hazard phrases refer to section 16.				

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: No special measures required.
- · After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

 $^{\cdot}$ 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

IE-EN

(Contd. on page 4)

www.griffon.eu 3/12



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.08.2022 Version number 31 (replaces version 30) Revision: 18.08.2022

Trade name: GRF GALVATEC ZINCSPRAY AE 400ML*12 L222

(Contd. of page 3)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingred	lients	with	limit '	values	that	: requi	ire mo	nitorin	g at	the wor	kplace:

67-64-1 acetone

OEL (Ireland) Long-term value: 1210 mg/m³, 500 ppm

IOELV

IOELV (EU) Long-term value: 1210 mg/m³, 500 ppm

106-97-8 n-Butan

OEL (Ireland) Short-term value: 1000 ppm

1330-20-7 xylene

OEL (Ireland) Short-term value: 442 mg/m³, 100 ppm

Long-term value: 221 mg/m³, 50 ppm

Sk, ĬOELV

IOELV (EU) Short-term value: 442 mg/m³, 100 ppm

Long-term value: 221 mg/m³, 50 ppm

Skin

(Contd. on page 5)

- IE-EN

www.griffon.eu 4/12



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.08.2022 Version number 31 (replaces version 30) Revision: 18.08.2022

Trade name: GRF GALVATEC ZINCSPRAY AE 400ML*12 L222

		(Contd. of page 4)					
74-98-6 pro	74-98-6 propane						
OEL (Ireland	OEL (Ireland) Asphx						
100-41-4 etl	hylbenzene						
OEL (Ireland	OEL (Ireland) Short-term value: 884 mg/m³, 200 ppm Long-term value: 442 mg/m³, 100 ppm Sk, IOELV						
IOELV (EU)	IOELV (EU) Short-term value: 884 mg/m³, 200 ppm Long-term value: 442 mg/m³, 100 ppm Skin						
75-28-5 isol	butane						
OEL (Ireland	d) Short-term value: 1000 ppm						
· DNELs							
67-64-1 ace	tone						
Oral C	Consumer, oral, longterm exposition	62 mg/kg bw/day					
Dermal C	Consumer, dermal, longterm exposition	62 mg/kg bw/day					
Inhalative C	Inhalative Consumer, inhalation, longterm exposition 200 mg/m³						
· PNECs	PNECs						
67-64-1 ace	67-64-1 acetone						
Fresh water	Fresh water 10.6 mg/l						
Marine wate	r 1.06 mg/l						
Soil	Soil 29.5 mg/kg						

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

- · Recommended filter device for short term use: Filter AX
- · Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Recommended thickness of the material: > 0,12 mm

Nitrile rubber, NBR

(Contd. on page 6)

IE-EN

www.griffon.eu 5/12



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.08.2022 Version number 31 (replaces version 30) Revision: 18.08.2022

Trade name: GRF GALVATEC ZINCSPRAY AE 400ML*12 L222

(Contd. of page 5)

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

· Eye/face protection Safety glasses



Tightly sealed goggles

Body protection: Use protective suit.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol

· Colour: According to product specification

Odour: Characteristic
Odour threshold: Not determined.

• Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range 55.8-56.6 °C Flammability Not applicable.

· Lower and upper explosion limit

Lower: 1.1 Vol %
Upper: 13 Vol %
Flash point: -97 °C
Ignition temperature: 365 °C

• Decomposition temperature: Not determined. • pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined. Vapour pressure at 20 °C: 8300 hPa

Density and/or relative density

Density at 20 °C: 0.97 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

• **9.2 Other information** All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

(Contd. on page 7)

IE-EN

www.griffon.eu 6/12



Safety data sheet according to 1907/2006/EC, Article 31

Version number 31 (replaces version 30) Revision: 18.08.2022 Printing date 18.08.2022

Trade name: GRF GALVATEC ZINCSPRAY AE 400ML*12 L222

(Contd. of page 6)

· Appearance:

· Form: Aerosol

· Important information on protection of health

and environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

Organic solvents: 67.3 % · Solids content: 31.5 %

· Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard

classes · Explosives Void Flammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised

container: May burst if heated.

· Oxidising gases Void · Gases under pressure Void Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void

· Substances and mixtures, which emit Void flammable gases in contact with water · Oxidising liquids Void · Oxidising solids Void Organic peroxides Void Void · Corrosive to metals Void Desensitised explosives

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

IE-EN

(Contd. on page 8)

7/12 www.griffon.eu



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.08.2022 Version number 31 (replaces version 30) Revision: 18.08.2022

Trade name: GRF GALVATEC ZINCSPRAY AE 400ML*12 L222

(Contd. of page 7)

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 ·	· LD/LC50 values relevant for classification:				
67-64-1 ad	67-64-1 acetone				
Oral	LD50	5800 mg/kg (rat)			
Dermal	LD50	20000 mg/kg (rabbit)			
106-97-8 ւ	106-97-8 n-Butan				
Inhalative	LC50/4 h	658 mg/l (rat)			
1330-20-7	xylene				
Oral	LD50	4300 mg/kg (rat)			
Dermal	LD50	2000 mg/kg (rabbit)			
100-41-4	100-41-4 ethylbenzene				
Oral	LD50	3500 mg/kg (rat)			
Dermal	LD50	17800 mg/kg (rabbit)			

· Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 9)

- IE-EN

www.griffon.eu 8/12



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.08.2022 Version number 31 (replaces version 30) Revision: 18.08.2022

Trade name: GRF GALVATEC ZINCSPRAY AE 400ML*12 L222

(Contd. of page 8)

- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Very toxic for fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR/ADN, IMDG, IATA UN1950

14.2 UN proper shipping name

· ADR/ADN 1950 AEROSOLS

· IMDG AEROSOLS, MARINE POLLUTANT

· IATA AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· ADR/ADN



· Class 2 5F Gases.

· Label 2.1

(Contd. on page 10)

www.griffon.eu 9/12



Safety data sheet according to 1907/2006/EC, Article 31

Version number 31 (replaces version 30) Revision: 18.08.2022 Printing date 18.08.2022

Trade name: GRF GALVATEC ZINCSPRAY AE 400ML*12 L222

(Contd. of page 9)

·IMDG



· Class 2.1 Gases. · Label 2.1

IATA



2.1 Gases. · Class 2.1

· Label

· 14.4 Packing group

· ADR/ADN, IMDG, IATA not regulated

· 14.5 Environmental hazards:

· Marine pollutant:

Symbol (fish and tree) Symbol (fish and tree)

· Special marking (ADR/ADN): · 14.6 Special precautions for user Warning: Gases.

· Hazard identification number (Kemler code): -

· EMS Number: F-D,S-U

SW1 Protected from sources of heat. · Stowage Code

> SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

SG69 For AEROSOLS with a maximum capacity Segregation Code

of 1 litre:

Segregation as for class 9. Stow "separated from"

class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of

class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

· 14.7 Maritime transport in bulk according to

IMO instruments Not applicable.

· Transport/Additional information:

Quantity limitations On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg

(Contd. on page 11)

IE-EN

10/12 www.griffon.eu



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.08.2022 Version number 31 (replaces version 30) Revision: 18.08.2022

Trade name: GRF GALVATEC ZINCSPRAY AE 400ML*12 L222

(Contd. of page 10)

	(Contd. of page 10
· ADR/ADN	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
, ,	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
·IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
,	Not permitted as Excepted Quantity
Remarks:	Under certain conditions substances in Class
	(flammable liquids) can be classified in
	packinggroup III.
	See IMDG, Part 2, Chapter 2.3, Paragraph 2.3.2.2
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALL
	HAZARDOUS
	11/12/11/2000

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E1 Hazardous to the Aquatic Environment

P3a FLAMMABLE AEROSOLS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Regulation (EC) No 273/2004 on drug precursors

67-64-1 acetone

3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

67-64-1 acetone

3

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 12)

IE-EN -

www.griffon.eu 11/12



Safety data sheet according to 1907/2006/EC, Article 31

Version number 31 (replaces version 30) Revision: 18.08.2022 Printing date 18.08.2022

Trade name: GRF GALVATEC ZINCSPRAY AE 400ML*12 L222

(Contd. of page 11)

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Aerosols	Bridging principles
Skin corrosion/irritation Serious eye damage/eye irritation Hazardous to the aquatic environment - short- term (acute) aquatic hazard Hazardous to the aquatic environment - long- term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: Bison QESH

Contact: Reach coordinator

Date of previous version: 22.01.2022 · Version number of previous version: 30

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

* Data compared to the previous version altered.

IE-EN

12/12 www.griffon.eu