



Express Pointing Mortar

READY TO USE MORTAR FOR MASONRY JOINTS

Date: 12 August 2019

Fact Sheet No.:TDS02088

YOUR SMART ADVANTAGES

- Ready to use, quick and easy to apply with a cartridge gun
- Produces durable, weather resistant joints
- Overpaintable with water based & synthetic paints

USES

Bostik Express Pointing Mortar has been specially developed to quickly repair damaged masonry joints in brick and stonework, without having to mix mortar. It can also be used to seal between stones, brick slips and around lead flashing.

It is supplied ready to use and is easily applied with a cartridge gun, internally or externally. It does not require a primer on most substrates, even on slightly damp surfaces. It can be overpainted where required.

PRODUCT CHARACTERISTICS

Colour	Cement grey
Form	Gunnable paste
Specific Gravity	1.66 g/ml
Composition	Acrylic dispersions and additives
Product Code	30615032 310ml cartridges x 12
Storage/Shelf Life	Up to 12 months from date of manufacture, when stored in original, unopened packaging in a cool, dry place within the temperature range +5°C to +25°C and out of direct sunlight. Protect from frost.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +40°C
Coverage	6 linear metres (approx.) per cartridge of joint 10mm in height x 5mm depth

Drying Times

Working time: up to 10 minutes
 Surface set: 5 hours
 Full cure: Cures at 2mm per 24 hrs (23°C @ 50% RH)
 Note: Drying times are affected by weather conditions and ambient temperatures. Low temperatures and/or wet weather will extend drying times.

Shore (A) Hardness

80
(DIN 53505)

Flow

< 2mm
(ISO 7390)

Shrinkage

5%

Cleaning

Clean tools and equipment with warm water immediately after use. Dried product can only be removed mechanically.

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Express Pointing Mortar, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

1. Joint surfaces must be clean, dry (or only slightly damp), sound and free from dust, oil, grease, loose material and other contaminants that may impair adhesion. Ensure the joint is a minimum of 5mm deep.
2. Oil and grease should be removed from non-porous substrates using a suitable cleaner.
3. Do not apply in direct sunlight.
4. Always test on a small inconspicuous area first and allow to fully dry before proceeding to full application. The test area should be examined after 24 hours to assess the colour suitability and adhesion to brickwork.

APPLICATION

- Using a sharp knife carefully cut off the dome of the cartridge, making sure not to damage the thread. Then screw on the V-nozzle supplied with the cartridge.
- Insert the cartridge into a cartridge gun by pressing the release plate and pulling out the plunger. Insert cartridge and repeatedly squeeze the trigger until the mortar appears.
- Place the nozzle at the start of the gap, with the V-shape facing inwards towards the joint and gently squeeze the trigger. Push forward slowly, ensuring a good solid fill of at least 5mm depth, by forcing the mortar into the joint. At the end of the run, release the trigger and press the plunger release plate on the gun.
- After 5 minutes, press the mortar into the joint using an appropriate jointing tool or rounded piece of wood.
- After a further 5-10 minutes, remove excess mortar from the joints and brickwork with a hand brush or wet sponge.
- Protect the mortar from rain for at least 5 hours after application. During curing, the product becomes darker.

PAINTABILITY

- Once Express Pointing Mortar is completely cured, it is overpaintable with water based and synthetic paints. Painting before full curing can cause the paint to crack.
- Always test for paint compatibility on a small inconspicuous area and examine after 24 hours, before full application.

CLEANING

- Clean tools and equipment with warm water before the mortar has dried. Dried product can only be removed mechanically.

PRECAUTIONS IN USE

Bostik Express Pointing Mortar is not suitable for continuous exposure to water.

It is not suitable for PE, PP, PMMA, PTFE, soft plastics, neoprene and bituminous substrates. It is also not suitable for movement joints.

Colour indicated on pack is a guide only. It is recommended that users apply a small amount of mortar and allow to dry to determine colour suitability before commencing work. Shade variations may occur between different batches. When completing projects requiring multiple cartridges, please ensure they are from the same batch.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and

Safety Data sheet for Bostik Express Pointing Mortar, available at www.bostik.com/uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company, which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability, which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use, which is inappropriate, or use, which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDSs, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com