



## Staffordshire Slate Blue Smooth A2232A

Declaration includes Special Shapes listed in BS4729 and Ibstock variants to Category II System 4

Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **Facing and rendered masonry, load bearing or non-loadbearing masonry structures including internal linings and partitions for building and civil engineering.**


U for use in Unprotected Masonry

Registered office  
Ibstock Brick Limited. Leicester Road. Ibstock Leicestershire. LE67 6HS

Attestation of Conformity System 2+

Notified factory production certification body 1020.CPR/ 10044845 **Technicky A Zkusebni Ustav Stavebni Praha s.p** performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, and issued the certificate of constancy of conformity of the factory production control.

Notified factory production certification body 1020.CPR/ 10044845 **Technicky A Zkusebni Ustav Stavebni Praha s.p** performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, and issued the certificate of constancy of conformity of the factory production control.

Declared Performance Essential Characteristics	Performance		Harmonised Technical Specification
Dimensions and tolerance mm	215x102x65		The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer. Signed for and on behalf of the manufacturer by:  Andy Batterham - Technical & Innovation Director Ibstock Brick Limited  
	Tolerance	T2	
	Range	R1	
Configuration	Vertically Perforated		
Group	HD units Group 2 Structural		
Flatness of bed faces	NPD		
Plane parallelism	NPD		
Compressive Strength (tested normal to the bed face of the unit) N/mm <sup>2</sup>	Mean	75	
	Normalised	76.5	
	Category	Cat I	
Dimensional Stability mm/m	NPD		
Bond Strength fixed N/mm <sup>2</sup>	0.15		
Active Soluble Salts	S2		
Reaction to Fire	Euro Class A1	Commission Decision 2000/605/EC	
Water absorption %	7		
Water vapour permeability	50/100μ		
Direct airborne sound insulation	1650		
Thermal conductivity W/mk	1.19		
Durability against freeze thaw	F2		
Dangerous substances	NPD		

Data correct since: 01/02/2022

For data prior to this date please contact technical@ibstock.co.uk

Downloaded: 20/2/2023