

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

# BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020

Revision date 30-Jan-2020 Revision Number 2.01

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

 1.1. Product Identifier

 Product Name
 BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

 Pure substance/mixture
 Mixture

 1.2. Relevant identified uses of the substance or mixture and uses advised against
 Coatings and paints, thinners, paint removers.

 Recommended use
 Coatings and paints, thinners, paint removers.

 Uses advised against
 None known

1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

#### E-mail address

SDS.box-EU@bostik.com

#### 1.4. Emergency telephone number

United Kingdom Ireland +44 (1785) 272650 +353 (1) 8624900 (Monday- Friday 9am-5pm)

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Specific target organ toxicity (single exposure)	Category 3 - (H336)
Specific target organ toxicity — repeated exposure	Category 1 - (H372)
Chronic aquatic toxicity	Category 2 - (H411)
Flammable liquids	Category 3 - (H226)

#### 2.2. Label Elements

Contains: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)



Signal word DANGER

#### Hazard statements

H336 - May cause drowsiness or dizziness H372 - Causes damage to organs through prolonged or repeated exposure

#### BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020

Revision date 30-Jan-2020 Revision Number 2.01

H411 - Toxic to aquatic life with long lasting effects

H226 - Flammable liquid and vapour

### **EU Specific Hazard Statements**

EUH066 - Repeated exposure may cause skin dryness or cracking

#### **Precautionary statements**

P101 - If medical advice is needed, have product container or label at hand

- P102 Keep out of reach of children
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P260 Do not breathe vapour
- P271 Use only outdoors or in a well-ventilated area
- P273 Avoid release to the environment
- P280 Wear protective gloves and eye/face protection
- P312 Call a POISON CENTER or doctor if you feel unwell
- P391 Collect spillage
- P403 + P233 Store in a well-ventilated place. Keep container tightly closed
- P405 Store locked up
- P501 Dispose of contents/container to an approved waste disposal plant

#### Additional information

This product requires tactile warnings if supplied to the general public. This product requires child resistant fastenings if supplied to the general public.

#### 2.3. Other Hazards

In use may form flammable/explosive vapour-air mixture

#### PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Not applicable

### 3.2. Mixtures 3.2 Mixtures

Chemical name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	RR-91855-8	>25 - <40	STOT SE 3 (H336) STOT RE 1 (H372) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 3 (H226) (EUH066)		01-2119458049- 33-XXXX

#### Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020

### SECTION 4: First aid measures 4.1. Description of first aid measures **General advice** Show this safety data sheet to the doctor in attendance. Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Eye contact Keep eye wide open while rinsing. Do not rub affected area. Wash off immediately with soap and plenty of water while removing all contaminated Skin contact clothes and shoes. Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Clean mouth with water. Drink 1 or 2 glasses of water. Call a doctor or poison control centre immediately. Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. 4.2. Most important symptoms and effects, both acute and delayed Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, Symptoms tiredness, nausea and vomiting.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media	Dry chemical. Carbon dioxide (CO2). Alcohol resistant foam.	
Unsuitable extinguishing media	Do not use straight streams. CAUTION: Use of water spray when fighting fire may be inefficient. Full water jet.	
5.2. Special hazards arising from t	he substance or mixture	
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.	
Hazardous combustion products	Carbon oxides.	
5.3. Advice for firefighters		
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.	

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

# BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Avoid breathing vapours or mists. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.
6.2. Environmental precautions	
Environmental precautions	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow to enter into soil/subsoil.
6.3. Methods and material for cont	ainment and cleaning up
Methods for containment	Dyke far ahead of spill; use dry sand to contain the flow of material. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers. Take up mechanically, placing in appropriate containers for disposal.
Prevention of secondary hazards	Eliminate all ignition sources if safe to do so.
6.4. Reference to other sections	
Reference to other sections	See section 8 for more information. See section 13 for more information.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. In case of insufficient ventilation, wear suitable respiratory equipment.
General hygiene considerations	Keep away from food, drink and animal feedingstuffs. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.
7.2. Conditions for safe storage, in	ncluding any incompatibilities
Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible

particular national regulations. Keep from freezing.

materials. Keep in an area equipped with sprinklers. Store in accordance with the

### 7.3. Specific end use(s)

#### Specific Use(s)

Coatings and paints, thinners, paint removers.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

# BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020

Revision date 30-Jan-2020 Revision Number 2.01

Other information

Observe technical data sheet.

# SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

**Exposure Limits** 

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

Chemical name	European Union	Ireland	United Kingdom
Asphalt	-	TWA: 0.5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>
8052-42-4		STEL: 10 mg/m <sup>3</sup>	STEL: 10 mg/m <sup>3</sup>

#### **Derived No Effect Level (DNEL)**

No information available

Derived No Effect Level (DNEL)		
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)		
Туре	worker Long term Systemic health effects	
Exposure route	Inhalation	
Derived No Effect Level (DNEL)	330 mg/m <sup>3</sup>	
Туре	worker Long term Systemic health effects	
Exposure route	Dermal	
Derived No Effect Level (DNEL)	44 mg/kg bw/d	

Derived No Effect Level (DNEL)		
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)		
Туре	Consumer Long term Systemic health effects	
Exposure route	Inhalation	
Derived No Effect Level (DNEL)	71 mg/m³	
Туре	Consumer Long term Systemic health effects	
Exposure route	Dermal	
Derived No Effect Level (DNEL)	26 mg/kg bw/d	
Туре	Consumer Long term Systemic health effects	
Exposure route	Oral	
Derived No Effect Level (DNEL)	26 mg/kg bw/d	

Predicted No Effect Concentration No information available. (PNEC)

8.2. Exposure controls

Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be **Engineering controls** exhausted directly at the point of origin. **Personal Protective Equipment** 

Eye/face protection	Tight sealing safety goggles.
Hand protection	Wear protective gloves. The breakthrough time of the gloves depends on the material
	and the thickness as well as the temperature. Recommended Use:. Polyvinyl chloride
	(PVC).
Skin and body protection	Gloves made of plastic or rubber. Antistatic footwear. Wear fire/flame resistant/retardant clothing.
Respiratory protection	In case of inadequate ventilation wear respiratory protection. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020

Revision date 30-Jan-2020 Revision Number 2.01

Recommended filter type:	Organic gases and vapours filter conforming to EN 14387.
Environmental exposure controls	Do not allow into any sewer, on the ground or into any body of water. Local authorities should be advised if significant spillages cannot be contained. Prevent product from entering drains.

# SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state Appearance Colour Odour Odour threshold	Liquid viscous Liquid Black Characteristic No information available	
<u>Property</u> pH Melting point / freezing point Boiling point / boiling range Flash point	Values No data available No data available >= 153 °C > 39 °C	<u>Remarks • Method</u>
Evaporation rate Flammability (solid, gas) Flammability Limit in Air	No data available Not applicable for liquids .	
Upper flammability or explosive limits Lower flammability or explosive limits	No data available	
Vapour pressure Vapour density Relative density Water solubility	No data available No data available No data available Insoluble in water	kPa
Solubility(ies) Partition coefficient Autoignition temperature	No data available No data available 200 °C	
Decomposition temperature Kinematic viscosity Dynamic viscosity Explosive properties	No data available > 370 mm <sup>2</sup> /s No data available No data available	@ 40°C
Oxidising properties 9.2. Other information Solid content (%)	No data available No information available	
Softening Point Molecular weight VOC Content (%) Density	No information available No information available <= 330 g/L No information available	
Bulk density	No information available	

# SECTION 10: Stability and reactivity

10.1. Reactivity	
Reactivity	No information available.
10.2. Chemical stability	
Stability	Stable under normal conditions.
Explosion Data Sensitivity to mechanical	None.

# BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020

impact Sensitivity to static discharge	Yes.	
10.3. Possibility of hazardous reac	tions	
Possibility of hazardous reactions	None under normal processing.	
10.4. Conditions to avoid		
Conditions to avoid	Heat, flames and sparks. Keep from freezing.	
10.5. Incompatible materials		
Incompatible materials	Oxidising agent.	
10.6. Hazardous decomposition products		
Hazardous decomposition products	None under normal use conditions. Stable under recommended storage conditions.	

## **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

### Information on likely routes of exposure

Product	Information
1100000	mornation

Inhalation	May cause drowsiness or dizziness.	
Eye contact	Based on available data, the classification criteria are not met.	
Skin contact	Based on available data, the classification criteria are not met.	
Ingestion	Based on available data, the classification criteria are not met.	
Symptoms related to the physical, chemical and toxicological characteristics		
Symptoms	Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.	

#### Numerical measures of toxicity

#### Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

#### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C9-C12,	LD50 >15000 mg/Kg (Rattus)	LD50 > 3400 mg/kg (Rattus)	LC50 (4hrs) >13.1 mg/l
n-alkanes, isoalkanes, cyclics,	OECD 401	OECD 402	(Rattus)
aromatics (2-25%)			
RR-91855-8			

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

#### BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE Supercedes Date: 29-Jan-2020

Serious eye damage/eye irritation	Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT - single exposure	May cause drowsiness or dizziness.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Based on available data, the classification criteria are not met.

# SECTION 12: Ecological information

#### 12.1. Toxicity

#### Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		Micro-organisms			(long-term)
Hydrocarbons, C9-C12,	EL50 (72h) =	10-30 mg/l	-	10-30mg/l		
n-alkanes, isoalkanes,	4.1 mg/l (			(daphnia		
cyclics, aromatics	Pseudokirchner			magna)		
(2-25%)	ella subcapitata)					
RR-91855-8	OECD 401					

### 12.2. Persistence and degradability

No information available. Persistence and degradability

#### 12.3. Bioaccumulative potential

**Bioaccumulation** No information available.

12.4. Mobility in soil

Mobility in soil No information available.

## 12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The components in this formulation do not meet the criteria for classification as PBT or vPvB.

### 12.6. Other adverse effects

Other adverse effects No information available.

BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE Supercedes Date: 29-Jan-2020 Revision date 30-Jan-2020 Revision Number 2.01

# SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture of weld containers.
European Waste Catalogue	17 03 02 bituminous mixtures other than those mentioned in 17 03 01 15 01 10*: Packaging containing residues of or contaminated by dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

# **SECTION 14: Transport information**

Note:	The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material. Keep from freezing.
Land transport (ADR/RID) 14.1 UN Number 14.2 Proper Shipping Name 14.3 Transport hazard class(es) Labels 14.4 Packing Group Description 14.5 Environmental hazards 14.6 Special Provisions Classification Code Tunnel restriction code Limited Quantity (LQ) ADR Hazard Id (Kemmler Number)	UN1999 Tars, liquid, Environmentally Hazardous 3 III UN1999, Tars, liquid, 3, III, (D/E), Environmentally Hazardous Yes None F1 (D/E) 5 L 30
<u>IMDG</u> 14.1 UN number 14.2 Proper Shipping Name	UN1999 Tars, liquid (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)), Marine Pollutant
14.3 Transport hazard class(es) 14.4 Packing group Description	3 III UN1999, Tars, liquid (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)), 3, III, (39°C c.c.), Marine Pollutant
<ul> <li>14.5 Marine Pollutant</li> <li>14.6 Special Provisions</li> <li>Limited Quantity (LQ)</li> <li>EmS-No.</li> <li>14.7 Transport in bulk according</li> </ul>	P. 955 5 L F-E, S-E
14.7 Transport in bulk according	to Annex II of MARPOL 73/78 and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)	
14.1 UN number	UN1999
14.2 Proper Shipping Name	Tars, liquid
14.3 Transport hazard class(es)	3
14.4 Packing group	III
Description	UN1999, Tars, liquid, 3, III
14.5 Environmental hazards	Yes
14.6 Special Provisions	A3

### BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020

Limited Quantity (LQ)	10 L
ERG Code	3L

### Section 15: REGULATORY INFORMATION

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

#### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

#### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

#### Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS P5b - FLAMMABLE LIQUIDS P5c - FLAMMABLE LIQUIDS E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

#### Persistent Organic Pollutants Not applicable

#### Not applicable

#### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## SECTION 16: Other information

#### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H336 - May cause drowsiness or dizziness

## BOSTIK FELTFIX BITUMINOUS FELT ADHESIVE

Supercedes Date: 29-Jan-2020

Revision date 30-Jan-2020 Revision Number 2.01

H372 - Causes damage to organs through prolonged or repeated exposure H411 - Toxic to aquatic life with long lasting effects Leaend SVHC: Substances of Very High Concern for Authorisation: Legend SECTION 8: Exposure controls/personal protection TWA (time-weighted average) TWA STEL STEL (Short Term Exposure Limit) Ceiling Maximum limit value Skin designation PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure EWC: European Waste Catalogue Key literature references and sources for data No information available Product Safety & Regulatory Affairs **Prepared By Revision date** 30-Jan-2020 Indication of changes Not applicable. **Revision note** Provide adequate information, instruction, and training for operator **Training Advice Further information** No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### **End of Safety Data Sheet**