

Kingston



SCAN HERE

Versatile, smooth facing brick.

The sophisticated Kingston Facing Bricks, are manufactured with a smooth vibrant finish. With five colour options, ranging from vivid red and gold tones to understated grey and stone shades, Kingston is suitable for any type of application.

- Manufactured with a smooth, sophisticated surface
- Vibrant long-lasting colours
- Suitable for both modern or period properties

 Ef-Stop®

S
Smooth
Finish

Autumn Gold



Burren



Moorland




Cottage Red



Charcoal



Slate



Size

Kingston



Specification

Product type	Concrete Facing Brick
Manufactured to	BS EN 771-3:2011
Brick type	Perforated (3 holes per brick)
Efflorescence	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
Strength	Compressive strength >22N/mm ²
Shrinkage (Moisture Movement)	0.64mm/m
Weight	2.7kg per brick (average)
Durability (Freeze/Thaw)	F2 (Severe Exposure)
Tolerances	Category D1
Reaction to fire	A1
Water absorption by capillary	2 g/m ² s
Water absorption	<7% water absorption on average
Soluble Salts	S2
Net dry density	2220 kg/m ³
Gross dry density	1930 kg/m ³
Shear bond strength	0.15N/mm ²
Thermal Conductivity	Protected 1.59W/m K Exposed 1.70 W/m K
Mortars & Expansion Joints	Refer to BS 5628-3:2005
Bed Reinforcement	Refer to BS 5628-3:2005
Specials	Range of complementary brick specials are available
Installed to	BS 5628-3:2005
B55	Plus F10 215 Create 45-80-50/302
Applications	Please refer to Table 15 of PD 6697: 2010. For further details please refer to www.tobermore.co.uk
Energy used	100% renewable energy
Water used	100% from our rainwater harvesting system and groundwater bore hole
Recycled content	Not less than 8%
Carbon footprint	0.32kgCo ² e/m ²
Recyclable	100% of this product can be recycled
Manufacturing & Delivery	From one location within the UK
breeam rating www.bre.co.uk	A+ , according to the Green Guide to Specification, 4th Edition 2009.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 Quality Management. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BES 6001.

Stock

product	size (mm)	colours available	in stock	no. per pack	no. per slice	weight kg per pack GB	weight kg per pack NI/ROI
Kingston BIM	215 x 100 x 65	Autumn Gold, Burren, Charcoal, Cottage Red, Moorland, Slate	YES	440	44	1198	1220

BIM - This product is available to download from our website in BIM Level 2 format.

Contact Us

GB: 0844 800 5736
NI: 028 7964 2411
ROI: 048 7964 2411

Email

technical@tobermore.co.uk
sales@tobermore.co.uk

tobermore.co.uk