

# Lansdowne



SCAN HERE

## Rustic effect facing brick.

Lansdowne facing brick is manufactured with a warm and aged feel. Lansdowne bricks are known for their hard-wearing capabilities and exceptional long-lasting colours.

- Tumbled to give an aged, rustic appearance
- Evokes timeless warmth and elegance
- Vibrant long-lasting colours
- Suitable for both modern and period properties



**A**  
Aged  
Finish

**Autumn Gold**



**Burren**



**Heather**




**Cottage Red**



**Charcoal**



**Slate**



**Size**

# Lansdowne



## Specification



<b>Product type</b>	Concrete Facing Brick
<b>Manufactured to</b>	BS EN 771-3:2011
<b>Manufacturing process</b>	Processed to give aged appearance
<b>Brick type</b>	Perforated (3 holes per brick)
<b>Efflorescence</b>	Minimum 12 hour vapour curing to significantly reduce the possibility of efflorescence
<b>Strength</b>	Compressive strength >22N/mm <sup>2</sup>
<b>Shrinkage</b> (Moisture Movement)	0.44mm/m
<b>Weight</b>	2.7kg per brick (average)
<b>Durability</b> (Freeze/Thaw)	F2 (Severe Exposure)
<b>Tolerances</b>	Category D1
<b>Reaction to fire</b>	A1
<b>Water absorption by capillary</b>	2 g/m <sup>2</sup> s
<b>Water absorption</b>	<7% water absorption on average
<b>Soluble Salts</b>	S2
<b>Net dry density</b>	2220 kg/m <sup>3</sup>
<b>Gross dry density</b>	1930 kg/m <sup>3</sup>
<b>Shear bond strength</b>	0.15N/mm <sup>2</sup>
<b>Thermal Conductivity</b>	Protected 1.59W/m K Exposed 1.70 W/m K
<b>Mortars &amp; Expansion Joints</b>	Refer to BS 5628-3:2005
<b>Bed Reinforcement</b>	Refer to BS 5628-3:2005
<b>Specials</b>	Range of complementary brick specials are available
<b>Installed to</b>	BS 5628-3:2005
<b>BS</b>	<b>Plus</b> F10 215 <b>Create</b> 45-80-50/302
<b>Applications</b>	Please refer to Table 15 of PD 6697: 2010. For further details please refer to <a href="http://www.tobermore.co.uk">www.tobermore.co.uk</a>
<b>Energy used</b>	100% renewable energy
<b>Water used</b>	100% from our rainwater harvesting system and groundwater bore hole
<b>Recycled content</b>	Not less than 10%
<b>Carbon footprint</b>	0.31kgCo <sub>2</sub> e/m <sup>2</sup>
<b>Recyclable</b>	100% of this product can be recycled
<b>Manufacturing &amp; Delivery</b>	From one location within the UK
<b>breeam rating</b> <a href="http://www.bre.co.uk">www.bre.co.uk</a>	<b>A+</b> , according to the Green Guide to Specification, 4th Edition 2009.

Tobermore products are manufactured in accordance with an accredited ISO 9001:2015 Quality Management. Manufacturing facilities are accredited to ISO14001:2015 Environmental Management. The company publish environmental labels and declarations in accordance with BES 6001.

## Stock

product	size (mm)	colours available	in stock	no. per pack	no. per slice	weight kg per pack GB	weight kg per pack NI/ROI
<b>Lansdowne</b>	215 x 100 x 65	Autumn Gold, Burren, Charcoal, Cottage Red, Heather, Slate	Yes	480	96	1306	1360

### Contact Us

GB: 0844 800 5736  
NI: 028 7964 2411  
ROI: 048 7964 2411

### Email

[technical@tobermore.co.uk](mailto:technical@tobermore.co.uk)  
[sales@tobermore.co.uk](mailto:sales@tobermore.co.uk)

[tobermore.co.uk](http://tobermore.co.uk)