

# Technical Data Sheet

Date of compilation: 08/06/2023

## ARC PLASTER & JOINT COMPOUND

### DESCRIPTION

Arc Plaster & Joint Compound is suitable for repairs on plaster and plasterboard prior to decorating. It has excellent wet adhesion making it easy to apply, will not slump on vertical surfaces and can be easily smoothed. It will cover holes up to 3mm deep.



### PREPARATION

Surfaces should be sound, dry, clean and free from damp, dust and grease. Surfaces painted with gloss should be sanded to provide a key. Nail heads in plasterboard should be knocked below the surface level and covered with an oil-based paint to prevent rusting.

### APPLICATION

Apply Arc Plaster & Joint Compound to the surface using a large brush, trowel or other suitable spreader. After the initial setting the surface can be smoothed over using a wet trowel. Alternatively, the surface can be allowed to dry thoroughly and smoothed down using fine sandpaper. When the surface is dry, it can be painted or wallpapered over. Surfaces should be sealed with a plaster sealer or sealer/PVA mix before wallpapering.

### TECHNICAL DATA

Measurement	Value	Test Method
Physical State	Paste	Visual
Colour	White	Visual
Odour	PVA Type	
Flash point	Not Applicable	
VOC content	None	
Viscosity	2800 - 3300	Helipath TF/Sp10
pH	7.2 - 8.0	
Specific Gravity	1.690 - 1.790	

### CLEANING & STORAGE

After use, ensure lid is firmly replaced. Clean tools with water before plaster sets hard.  
PROTECT FROM FROST.

# Technical Data Sheet

Date of compilation: 08/06/2023

## ARC PLASTER & JOINT COMPOUND

### HEALTH AND SAFETY

See MSDS for full information.

### NOTE

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Full information and advice is freely available from our Technical Services Department e-mail [technical@arcbuildingproducts.ie](mailto:technical@arcbuildingproducts.ie). Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of supplied product.